

NASA CR-176994

NASA-CR-176994
19860019487

A Reproduced Copy OF

N86-28959

LIBRARY COPY

NOV 14 1986

LANGLEY RESEARCH CENTER
LIBRARY, NASA
HAMPTON, VIRGINIA

Reproduced for NASA
by the
NASA Scientific and Technical Information Facility



NF01698

FFNo 672 Aug 65

(NASA-CR-176994) FLUTTER PREDICTION FOR A
WING WITH ACTIVE AILERON CONTROL Final
Report (California Polytechnic State Univ.)
112 p

CSCI 01C

N86-28959

G3/08 Unclass
43346

FLUTTER PREDICTION FOR A WING
WITH ACTIVE AILERON CONTROL

FINAL REPORT

PRINCIPAL INVESTIGATORS

Kevin Penning

Doral E. Sandlin

June 1983

California Polytechnic State University
Aeronautical Engineering Department
San Luis Obispo, California

Grant No. NCC4-1

N86-28959#

TABLE OF CONTENTS

| | Page |
|--|------|
| LIST OF TABLES | iii |
| LIST OF FIGURES | iv |
| ABSTRACT | v |
| NOMENCLATURE | vi |
| CHAPTER | |
| 1 INTRODUCTION | 1 |
| 2 VIBRATION MODEL OF WING IN STILL AIR | 3 |
| 3 AERODYNAMIC INFLUENCE COEFFICIENTS | 8 |
| 4 CONTROL LAW | 12 |
| 5 INCLUDING CONTROL LAW IN VIBRATION EQUATIONS | 15 |
| 6 ANALYSIS OF DAST ARW-1 | 22 |
| 7 FLIGHT TEST DATA | 24 |
| 8 RESULTS | 26 |
| 9 CONCLUSIONS | 28 |
| APPENDIX | |
| A TABLES AND FIGURES | 29 |
| B INPUT DOCUMENTATION FOR PROGRAM "SAFSS" | 38 |
| C LISTING OF PROGRAM "SAFSS" | 47 |
| D SAMPLE INPUT FILE | 85 |
| E SAMPLE OUTPUT | 93 |
| BIBLIOGRAPHY | 104 |

LIST OF TABLES

| Table | | Page |
|-------|--|------|
| 1 | Natural Frequencies of Vibration Modes | 30 |
| 2 | Vibration Frequencies for FSS Off | 30 |
| 3 | Vibration Frequencies for FSS On | 31 |

LIST OF FIGURES

| Figure | | Page |
|--------|--|------|
| 1 | DAST ARW-1 Vehicle Platform | 30 |
| 2 | Flow Diagram of Program "SAFSS" | 31 |
| 3 | Flow Diagram of main subroutine of "SAFSS" | 32 |
| 4 | Block Diagram of Computer Programs Part 1 | 33 |
| 5 | Block Diagram of Computer Programs Part 2 | 34 |
| 6 | Control Law for DAST ARW-1 Flight Test 3 | 35 |
| 7 | Root Locus versus Mach Number | 36 |

Nomenclature

| | |
|-----------|--|
| a | subscript represents aileron mode |
| a_n | accelerometer signal |
| A, G, H | control law matrices |
| b | semi-span of the wing |
| b_a | aileron mode damping (from control law) |
| d_{ii} | ii element of generalized damping matrix |
| D | generalized damping matrix |
| d_i | damping factor of i 'th mode |
| D | modal accelerometer deflection matrix |
| $g(s)$ | portion of control law used for aileron mode |
| $G(s)$ | entire control law |
| $G'(s)$ | portion of control law not used for aileron mode |
| I | identity matrix |
| ω | reduced frequency |
| k_a | aileron mode stiffness (from control law) |
| k_{ii} | ii element of generalized stiffness matrix |
| K | generalized stiffness matrix |
| L | generalized force matrix |
| $L(s)$ | generalized force matrix in Laplace form |
| m | mass of the aileron |
| m_{ii} | ii element of generalized mass matrix |

m_{ij} ij element of generalized mass matrix
 M generalized mass matrix
 $P_1, P_2,$ matrices representing aerodynamic influence
 P_3, R_0 coefficients
 $P_1', P_2',$ nondimensional matrices representing aerodynamic
 P_3', R_0' influence coefficients
 q dynamic pressure
 $Q(s)$ aerodynamic influence coefficient matrix in
 Laplace form
 $Q(s')$ nondimensional aerodynamic influence
 coefficient matrices in Laplace form
 $r_i(x,y)$ deflection at point (x,y) for the i 'th mode
 r_{il} leading edge deflection of aileron for i 'th mode
 r_{it} trailing edge deflection of aileron for i 'th mode
 r_k modal deflection at accelerometer location
 u_i i 'th mode displacement vector
 u_i' first derivative of i 'th mode displacement vector
 u_i'' second derivative of i 'th mode displacement vector
 U displacement vector matrix
 U' first derivative of displacement vector matrix
 U'' second derivative of displacement vector matrix
 v free stream velocity
 w frequency of oscillation
 w_i natural frequency of i 'th vibration mode
 y_i i 'th control law state vector
 Y control law state vector matrix
 X generalized force state vector matrix
 $P(x,y)$ density of aircraft at point (x,y)

CHAPTER 1

INTRODUCTION

The ability to predict the aeroelastic response of aircraft wings is of increasing importance as attempts are made to reduce the weight of aircraft wings. One of the methods presently being explored to reduce weight is the use of a flutter suppression system (FSS) to reduce the required structural stiffness of the wing. The wing must be stiff enough to remain vibrationally stable (positive damping) throughout its flight envelope. If the wing is not vibrationally stable, it will flutter and possibly cause the loss of the aircraft.

This paper explains a method for predicting the vibrational stability of an aircraft with an analog active aileron FSS. Active aileron refers to the use of an active control system connected to the aileron to damp vibrations. Wing vibrations are sensed by accelerometers and the information is used to deflect the aileron. Aerodynamic forces caused by the aileron deflection oppose wing vibrations and effectively add additional damping to the system.

An assumed mode vibrational analysis approach is used with additional terms added to include the unsteady aerodynamics of a vibrating wing and the control system feedback. The assumed modes used are the actual vibration modes of the aircraft plus an aileron mode. The unsteady aerodynamic affects, modeled by the third order pade approximation method suggested by Edwards in the paper

ORIGINAL PAGE IS
OF POOR QUALITY

"Applications of Laplace Transform Methods to Airfoil Motion and Stability Calculations", are used as the forcing functions for the vibration.

A computer program called "SAFSS" was written to determine the vibrational stability of an aircraft wing using the method described above. The input information needed to use "SAFSS" consists of: the natural frequencies of vibration, the generalized mass for each mode, the generalized force matrices for the mach number of interest, the control law matrices and the aileron deflections for each mode. "SAFSS" produces a root locus plot from a CalComp plotter and a listing of the frequencies and damping.

A comparison between predicted and flight test data for the DAST ARW-1 vehicle is made. DAST stands for drones for aerodynamic and structural testing. ARW-1 stands for aeroelastic research wing number one. The DAST ARW-1 is a modified Firebee II target drone fuselage mated to the ARW-1 wing (see figure 1). ARW-1 is a supercritical, sweptback, transport-type wing with an aspect ratio of 6.8 and a performance design point of mach 0.98 at 45,000 feet. The ARW-1 wing is designed to be susceptible to flutter and is equipped with an active aileron flutter suppression system (FSS).

CHAPTER 2

VIBRATION MODEL OF WING IN STILL AIR

Since flutter is a vibration problem, it would seem to be a reasonable idea to start with a basic vibrational approach and work up to the harder aspects one at a time. This section will review the basic equations of the "assumed modes" method (sometimes called Rayleigh-Ritz method) used to solved vibration problems.

An aircraft wing can be treated as a normal beam if no air is flowing over it. Because the aircraft is symmetrical, two types of vibration are possible: the symmetric case where both wings vibrate 180 degrees out of phase. The symmetric and asymmetric vibrations do not couple with eachother so two separate analyses will be run. The equations used to determine the frequencies and damping of the system are identical so no distinction is made between the symmetric and asymmetric cases.

Using the orthogonal normal modes (vibration modes) of the wing and generalized terms, each vibration mode can be written as a function of one variable and it's derivatives. The equations of motion are represented by

$$(m_i) * u_i'' + (b_i) * u_i' + (k_i) * u_i = 0$$

where " m_i " is the generalized mass, " b_i " is the generalized damping, " k_i " is the generalized stiffness with " i " represent the i 'th mode. Using the matrix notion:

$$\{U\} = \begin{Bmatrix} u_1 \\ u_2 \\ u_3 \\ \vdots \\ u_n \end{Bmatrix}$$

$$[M] = \begin{bmatrix} m_1 & 0 & 0 & \dots & 0 \\ 0 & m_2 & 0 & \dots & 0 \\ 0 & 0 & m_3 & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & 0 & m_n \end{bmatrix}$$

$$[B] = \begin{bmatrix} b_1 & 0 & 0 & \dots & 0 \\ 0 & b_2 & 0 & \dots & 0 \\ 0 & 0 & b_3 & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & 0 & b_n \end{bmatrix}$$

$$[K] = \begin{bmatrix} k_1 & 0 & 0 & \dots & 0 \\ 0 & k_2 & 0 & \dots & 0 \\ 0 & 0 & k_3 & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & 0 & k_n \end{bmatrix}$$

the vibration equations can be written as one matrix equation

$$[M]\{U''\} + [B]U' = [K]\{U\} = 0$$

Using the fact that $\{U'\}$ is equal to U' , and reordering the above equation, the vibration equations can be written as:

$$\begin{bmatrix} I & 0 \\ 0 & M \end{bmatrix} \begin{Bmatrix} U' \\ U'' \end{Bmatrix} = \begin{bmatrix} 0 & I \\ -K & -B \end{bmatrix} \begin{Bmatrix} U \\ U' \end{Bmatrix}$$

The left side of the above equations can be simplified by multiplying by the inverse of the left hand square matrix.

The inverse is

$$\begin{bmatrix} I & 0 \\ 0 & M \end{bmatrix}^{-1} = \begin{bmatrix} I & 0 \\ 0 & M^{-1} \end{bmatrix}$$

Since $[M]$ is a diagonal matrix, $[M]^{-1}$ is a diagonal matrix with terms equal to the inverse of the terms in $[M]$.

$$\begin{bmatrix} m_1 & 0 & . & . & 0 \\ 0 & m_2 & . & . & 0 \\ . & . & . & . & 0 \\ . & . & . & . & 0 \\ 0 & 0 & 0 & 0 & m_n \end{bmatrix}^{-1} = \begin{bmatrix} 1/m_1 & 0 & . & . & 0 \\ 0 & 1/m_2 & . & . & 0 \\ . & . & . & . & 0 \\ . & . & . & . & 0 \\ 0 & 0 & 0 & 0 & 1/m_n \end{bmatrix}$$

Multiplying both sides by the inverse solves the equations for the derivatives of "U".

$$\begin{Bmatrix} U' \\ U'' \end{Bmatrix} = \begin{bmatrix} 0 & I \\ -M & K \end{bmatrix} \begin{Bmatrix} U \\ U' \end{Bmatrix}$$

Because both $[M]^{-1}$ and $[K]$ are diagonal matrices, their product will also be a diagonal matrix.

$$[M]^{-1} [K] = \begin{bmatrix} k_1/m_1 & 0 & 0 & . & . & 0 \\ 0 & k_2/m_2 & 0 & . & . & 0 \\ 0 & 0 & k_3/m_3 & . & . & 0 \\ . & . & . & . & . & 0 \\ . & . & . & . & . & 0 \\ 0 & 0 & 0 & 0 & 0 & k_n/m_n \end{bmatrix}$$

The same statement holds true for the product of $[M]^{-1}$ and $[B]$.

$$[M]^{-1} [B] = \begin{bmatrix} b_1/m & 0 & 0 & \dots & 0 \\ 0 & b_2/m & 0 & \dots & 0 \\ 0 & 0 & b_3/m & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & \dots & b_n/m \end{bmatrix}$$

Two relationships that are helpful in solving vibration problems are

$$k_i/m_i = \omega_i^2$$

$$b_i/m_i = 2*d_i*\omega_i$$

where " ω " is the natural frequency and " d " is the damping factor. Substituting these relationships into the matrices

$$[M]^{-1} [K] = \begin{bmatrix} \omega_1^2 & 0 & 0 & \dots & 0 \\ 0 & \omega_2^2 & 0 & \dots & 0 \\ 0 & 0 & \omega_3^2 & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & \dots & \omega_n^2 \end{bmatrix}$$

$$[M]^{-1} [B] = \begin{bmatrix} 2*d_1*\omega_1 & 0 & 0 & \dots & 0 \\ 0 & 2*d_2*\omega_2 & 0 & \dots & 0 \\ 0 & 0 & 2*d_3*\omega_3 & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & \dots & 2*d_n*\omega_n \end{bmatrix}$$

The natural frequency for a structure can be obtained from any program that does vibrational analysis such as "NASIRAN" or from a ground vibration test (a test in which the structure is shaken). Damping factors are harder to come by theoretically so a value is usually assumed. The wing provides only a small amount of damping so a small value, such as 0.005, can be assumed.

CHAPTER 3

AERODYNAMIC INFLUENCE COEFFICIENTS

The oscillatory motion of an aircraft wing in flight will produce oscillatory forces on the wing. As the wing oscillates up and down, the deflection and its derivatives cause an effective angle of attack which changes the lifting forces on the wing. Likewise, as the wing oscillates torsionally, the changes in pitch and its derivatives will produce changes in the lift.

The oscillation of the lift on the wing acts as a forcing function to the wing vibration and must be included in the vibration equations. The lift can be included in the following manner

$$[M] \{\ddot{U}\} + [B] \{\dot{U}\} + [K] \{U\} = \{L\}$$

where $\{L\}$ represents the oscillatory aerodynamic loads (generalized forces). The aerodynamic loads can be defined in the Laplace form to be

$$L(s) = q * [Q(s)] * \{U\}$$

where "q" is the dynamic pressure and $[Q(s)]$ represents the aerodynamic influence coefficients.

The $[Q(s)]$ matrix is determined by curve fitting the aerodynamic influence coefficients (AICs) calculated at several vibrational frequencies. AICs for several reduced frequencies can be calculated by using a doublet lattice routine or some other unsteady aerodynamics routine. The

AICs are a function of the reduced frequency and the mach number. The reduced frequency (k) is defined as

$$k = (b * w) / v$$

where "b" is the semi-span, "w" is the frequency of oscillation and "v" is the free stream velocity. A nondimensional form of $[Q(s)]$ can be assumed to be

$$[Q(s')] = (s' + [R0'])^{-1} * ([P1'](s')^2 + [P2']s' + [P3'])$$

where $[P1']$, $[P2']$, $[P3']$ and $[R0']$ are constants determined by performing a least squares curve fit on the AICs calculated at the different reduced frequencies. The "s'" is used to indicate a function of reduced frequency instead of oscillatory frequency.

Rewriting this equation as a function of the oscillation frequency results in

$$[Q(s)] = (sI * b/v + [R0'])^{-1} * ([P1'](s * b/v)^2 + [P2']s * b/v + [P3'])$$

Multiplying $[Q(s)]$ by U and labeling the product $\{X\}$

$$\{X\} = [Q(s)]\{U\}$$

The above equations can be rewritten by substituting in for $[Q(s)]$ and rearranging

$$(sI + [R0'] * v/b) \{X\} = ([P1'](s)^2 * b/v + [P2']s + [P3'] * v/b) \{U\}$$

For the ease of writing and to agree with the nomenclature used by other authors the following notation will be used:

$$[R0] = v/b*[R0']$$

$$[P1] = b/v*[P1']$$

$$[P2] = [P2']$$

$$[P3] = v/b*[P3']$$

Note that [P1], [P2], [P3] and [R0] must be recalculated for each different mach number. Using the above notion and taking the previous equation out of Laplace form,

$$[I](X'') - [P1](U'') = -[R0](X) + [P3](U) + [P2](U')$$

Remembering that

$$[M](U'') + [B](U') + [K](U) = (L)$$

and

$$(L) = q * (X)$$

the vibration equations can be written as

$$\begin{bmatrix} I & 0 & 0 \\ 0 & M & 0 \\ 0 & -P1 & I \end{bmatrix} \begin{Bmatrix} U'' \\ U' \\ X' \end{Bmatrix} = \begin{bmatrix} 0 & I & 0 \\ -K & -B & qI \\ P3 & P2 & -R0 \end{bmatrix} \begin{Bmatrix} U \\ U' \\ X \end{Bmatrix}$$

Taking the inverse of the left hand side

$$\begin{bmatrix} I & 0 & 0 \\ 0 & M & 0 \\ 0 & -P1 & I \end{bmatrix}^{-1} = \begin{bmatrix} I & 0 & 0 \\ 0 & M^{-1} & 0 \\ 0 & P1*M^{-1} & I \end{bmatrix}$$

and multiplying both sides by the inverse

$$\begin{Bmatrix} U' \\ U'' \\ X' \end{Bmatrix} = \begin{bmatrix} I & 0 & 0 \\ 0 & M^{-1} & 0 \\ 0 & P1*M^{-1} & I \end{bmatrix} \begin{bmatrix} 0 & I & 0 \\ -K & -B & qI \\ P3 & P2 & -R0 \end{bmatrix} \begin{Bmatrix} U \\ U' \\ X \end{Bmatrix}$$

the vibration equations can be written as

$$\begin{Bmatrix} U' \\ U'' \\ X' \end{Bmatrix} = \begin{bmatrix} 0 & I & 0 \\ -M^{-1}K & -M^{-1}B & M^{-1}q \\ P3-P1*M^{-1}K & P2-P1*M^{-1}B & -R0+P1*M^{-1}q \end{bmatrix} \begin{Bmatrix} U \\ U' \\ X \end{Bmatrix}$$

The above equation can be used to solve for the frequency and damping of the open loop aircraft wing vibration.

CHAPTER 4

CONTROL LAW

Although the procedure for putting a control law into matrix form is fairly standard, a few steps can be taken to simplify the solution of the vibration equations. In addition, part of the control law must be used elsewhere in the analysis (see chapter 5).

A control law is defined as the output of a system divided by the input of a system. The input signal for this analysis is an accelerometer signal and the output is the deflection of the aileron. The numerator and denominator of the control law are generally written as the product of several first and second order Laplace polynomials (see figure 6). Part of the control law, a second order polynomial from the denominator and a constant from the numerator

$$g(s) = k / (s^2 + c*s + k)$$

where "k" and "c" are constants, must be used for the aileron vibration mode (see chapter 5). The entire control law is equal to the product of its parts so

$$G(s) = G'(s) * g(s)$$

where $G(s)$ is the entire control law, $G'(s)$ is the control law without the aileron term and $g(s)$ is the aileron term.

The portion of the control law that needs to be put into matrix form is $G'(s)$. Keeping in mind that the input to

$G'(s)$ is the accelerometer signal and the output is a state space vector, the following equation can be written

$$G'(s) = V(s)/a_n(s)$$

where "an" is the accelerometer signal and "V" is a state space vector. Taking $G'(s)$ out of the Laplace form and putting it into state vector differential equation form results in the following equation

$$\begin{aligned} \{Y'\} &= [A] Y + [G]\{a_n\} \\ \{V\} &= [H]\{Y\} \end{aligned}$$

where the matrices $[A]$, $[G]$ and $[H]$ have no unique solution but depend on the state vectors $\{Y\}$.

In order to keep the vibration equations as simple as possible, it is desirable to have $[G]$ and $[H]$ contain as many zeros as possible. If the denominator of $G'(s)$ is at least 3 orders larger than the numerator, $[G]$ and $[H]$ can be constructed to each contain only one non-zero term.

$G'(s)$ can be broken up into the product of its second order (or smaller) polynomials of the form

$$g'_n(s) = (s^2 + a*s + b) / (s^2 + c*s + d)$$

where $g'_n(s)$ is a portion of $G'(s)$, "a", "b", "c" and "d" are constants.

Assuming that $g'_1(s)$ is of the form

$$g'_1(s) = 1 / (s + d)$$

and $g'_2(s)$ is of the form

$$g_2'(s) = 1 / (s^2 + c*s + d)$$

[G] and [H] can be forced to have a minimum of terms. By assigning the state vectors {Y} to be the unlabeled inputs and outputs to each portion of the control law

$$g_1'(s) = y_1 / an$$

$$g_2'(s) = y_1 / y_1$$

the following equations can be written

$$y_1' = d*y_1 + an$$

$$y_2' = y_3$$

$$y_3' = y_1 - d*y_2 - c*y_3$$

Note that the accelerometer signal, "an" is used only once, meaning that [G] contains only one non-zero value. Assigning the state vectors {Y} in this manner also causes [H] to contain only one non-zero value.

CHAPTER 5

INCLUDING CONTROL LAW IN VIBRATION EQUATIONS

The movement of the aileron will have two effects on the vibration equations. The first will be the addition of a mode shape (the aileron mode) and the calculation of AICs for the mode. The second will be the introduction of nondiagonal terms to $[M]$ due to the addition of non-orthogonal aileron mode.

In order to include the aileron as a vibration mode, terms for the generalized mass, generalized stiffness, and damping term must be used. In the previous chapter the control law was divided up into two parts

$$G(s) = G'(s) * g(s)$$

where $G'(s)$ was put into state vector differential form and $g(s)$ was of the form

$$g(s) = \frac{k_a}{(s + b_a * s + k_a)}$$

As stated in the last chapter the output of $G'(s)$ is $\{V\}$. Since the output of $g(s)$ is the aileron deflection, the following equation must be true

$$g(s) = u_a / V$$

where u is the aileron deflection. Substituting for $g(s)$, to obtain

$$k_a * \{V\} = u_a'' + b_a * u_a' + k_a * u_a$$

Solving the above equation for " u_a'' "

$$u_a'' = -k_a * u_a - b_a * u_a' + k_a * V$$

The vibration mode for the aileron can than be defined as having a generalized mass of 1.0, a generalized stiffness of k_a , and a generalized damping term of b_a .

The input to the control law was described in the previous chapter as the signal from the accelerometer. The accelerometer signal is the acceleration at the accelerometer location. Since the vibration model is based on superposition, the acceleration at any point, due to the k'th vibration mode, is equal to the acceleration state vector for the k'th vibration mode multiplied by the deflection k'th mode shape at that point. Therefore,

$$a_n = \sum_k r_k * u_k''$$

where "an" is the accelerometer signal, " u_k'' " is the acceleration of the k'th vibration mode and " r_k " is the deflection at the accelerometer location for the k'th mode shape. Expressing "an" in matrix notation

$$\{a_n\} = [D] \{u_k''\}$$

where [D] is a row matrix containing the modal vibration deflections at the accelerometer location.

A conversion factor may be needed between the units of the analysis and the units of the control law. If the control law is designed to convert a signal from g's (acceleration of gravity) to degrees deflection of the aileron, and the units being used in the analysis are inches and seconds, a conversion between the model and the real system must be made. Using the above example, the control law would have the units

$$G(s) = AD \text{ (degrees)} / an \text{ (gravities)},$$

and the analysis would require the units:

$$G(s) = ua \text{ (modal deflection)} * c / an \text{ (in/sec}^2\text{)}$$

where $G(s)$ is the control law, "AD" is the aileron deflection, "u" is the state space notation for the aileron mode and "c" is the conversion factor. The conversion from g's to in/sec² is simply

$$1 \text{ g} = (32.2 \text{ ft/sec}^2) * (12 \text{ in/ft}) = 386.4 \text{ in/sec}^2$$

and assuming that a 10 degree deflection of the aileron is equivalent to the aileron mode

$$1 \text{ degree} = 1/10 \text{ deflection mode}$$

Therefore, the conversion factor is determined to be

$$c = (1/386.4) * (1/10)$$

The equations related to the aileron mode and control law are

$$\{Y'\} = [A]\{Y\} + [G]\{a_n\}$$

$$\{V\} = [H]\{Y\}$$

$$\{a_n\} = [D]\{U''\}$$

$$u_a'' = -k_a * u_a - b_a * u_a' + k_a * c_a * \{V\}$$

Combining the above equations, the following state vector equations can be obtained;

$$\{Y'\} = [A]\{Y\} + [G][D]\{U''\}$$

$$u_a'' = -k_a * u_a - b_a * u_a' + k_a * c_a * [H]\{Y\}$$

The aileron mode is not orthogonal to the other vibration modes so nondiagonal terms will be introduced into $[M]$ and/or $[K]$. In the case being examined here, there is no coupling between modes in $[K]$ but there is coupling in $[M]$. The terms in $[M]$ are defined as

$$m_{ij} = \iint r_i(x,y) * r_j(x,y) * \rho(x,y) dx dy$$

where " m_{ij} " is the element ij of the generalized mass matrix " r_i " and " r_j " are deflections at the point (x,y) due to the i 'th and j 'th mode shapes, and " ρ " is the density of the wing at point (x,y) . Because the deflection of the aileron mode is zero everywhere except the aileron, the integral will only be non-zero over the aileron. Assuming the aileron is rectangular and has a constant mass distribution, the generalized mass terms due to the aileron mode are

$$m_{ia} = -m \cdot r_{at} \cdot (r_{il}/3 + (r_{il} - r_{it})/2)$$

Where " m_{ia} " is the generalized mass of i 'th row and the column representing the aileron mode; " m " is the mass of the aileron; " r_{at} " is the deflection of the trailing edge of the aileron for the aileron mode shape; " r_{il} " is the deflection of leading edge of the aileron for the i 'th mode shape; and " r_{it} " is the deflection of the trailing edge of the aileron for the i 'th mode shape. Assuming that the aileron mode is placed last, $[M]$ would then be written as

$$[M] = \begin{bmatrix} m_1 & 0 & 0 & \dots & 0 & m_{1a} \\ 0 & m_2 & 0 & \dots & 0 & m_{2a} \\ 0 & 0 & m_3 & \dots & 0 & m_{3a} \\ \vdots & \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & 0 & \dots & m_n & m_{na} \\ 0 & 0 & 0 & \dots & 0 & 1 \end{bmatrix}$$

Putting the problem into state vector differential notation

$$\begin{bmatrix} I & 0 & 0 & 0 \\ 0 & M & 0 & 0 \\ 0 & -P1 & I & 0 \\ 0 & -GD & 0 & I \end{bmatrix} \begin{Bmatrix} U' \\ U'' \\ X' \\ Y' \end{Bmatrix} = \begin{bmatrix} 0 & I & 0 & 0 \\ -K & -B & qI & k_{aCH} \\ P3 & P2 & R0 & 0 \\ 0 & 0 & 0 & A \end{bmatrix} \begin{Bmatrix} U \\ U' \\ X \\ Y \end{Bmatrix}$$

The inverse of the square matrix on the left is

$$\begin{bmatrix} I & 0 & 0 & 0 \\ 0 & M & 0 & 0 \\ 0 & -P1 & I & 0 \\ 0 & -GD & 0 & I \end{bmatrix}^{-1} = \begin{bmatrix} I & 0 & 0 & 0 \\ 0 & M^{-1} & 0 & 0 \\ 0 & P1M^{-1} & I & 0 \\ 0 & GDM^{-1} & 0 & I \end{bmatrix}$$

Multiplying both sides by the inverse and simplifying

$$\begin{Bmatrix} U^* \\ U^{*'} \\ X^* \\ Y^* \end{Bmatrix} = \begin{bmatrix} 0 & I & 0 & 0 \\ -1 & -1 & -1 & -1 \\ -M^{-1}K & -M^{-1}B & M^{-1}q & M^{-1}kacH \\ P3-P1M^{-1}K & P2-P1M^{-1}B & -R0+P1M^{-1}q & P1M^{-1}kacH \\ -1 & -1 & -1 & -1 \\ -GDM^{-1}K & -GDM^{-1}B & GDM^{-1}q & A+GDM^{-1}kacH \end{bmatrix} \begin{Bmatrix} U \\ U^* \\ X \\ Y \end{Bmatrix}$$

Because of the aileron mode, the $[M^{-1}K]$, $[M^{-1}B]$ and $[M^{-1}q]$ are no longer diagonal. Assuming that the aileron mode is placed last

$$M^{-1}K = \begin{bmatrix} k/m & 0 & 0 & . & . & k * m / m \\ 1 & 1 & . & . & . & a \ 1a \ 1 \\ 0 & k/m & 0 & . & . & k * m / m \\ 0 & 2 & 2 & . & . & a \ 2a \ 2 \\ 0 & 0 & k/m & . & . & k * m / m \\ . & . & 3 & 3 & . & a \ 3a \ 3 \\ . & . & . & . & . & . \\ . & . & . & . & . & . \\ C & 0 & 0 & . & . & k \\ & & & & & a \end{bmatrix}$$

$$M^{-1}B = \begin{bmatrix} b/m & 0 & 0 & . & . & b * m / m \\ 1 & 1 & . & . & . & a \ 1a \ 1 \\ 0 & b/m & 0 & . & . & b * m / m \\ 0 & 2 & 2 & . & . & a \ 2a \ 2 \\ 0 & 0 & b/m & . & . & b * m / m \\ . & . & 3 & 3 & . & a \ 3a \ 3 \\ . & . & . & . & . & . \\ . & . & . & . & . & . \\ 0 & 0 & 0 & . & . & b \\ & & & & & a \end{bmatrix}$$

$$M^{-1}q = \begin{bmatrix} q/m_1 & 0 & 0 & . & . & 0 & 0 \\ 0 & q/m_2 & 0 & . & . & 0 & 0 \\ 0 & 0 & q/m_3 & . & . & 0 & 0 \\ . & . & . & . & . & . & . \\ . & . & . & . & . & . & . \\ 0 & 0 & 0 & . & . & q/m_n & 0 \\ 0 & 0 & 0 & . & . & 0 & 0 \end{bmatrix}$$

This is the form of the vibration equations that will be used to solve for the frequency and damping of an aircraft wing.

ORIGINAL PAGE IS
OF POOR QUALITY

CHAPTER 6

ANALYSIS OF DAST ARW-1

The computer program "SAFSS" (Stability Analysis of Flutter Suppression Systems) was written to implement the analysis approach presented in chapters 2-5 (see figures 2 and 3). The input information to "SAFSS" consists of the generalized force matrices, the control law matrices, the generalized mass, natural frequency, and the aileron deflections for each mode. In order to obtain the input information, other computer programs were used.

The finite element analysis portion of the computer program "NASTRAN" and an input file provided by NASA Langley were used to calculate the first ten natural frequencies and mode shapes of the DAST ARW-1. The aileron mode shape was then substituted for one of the rigid body modes calculated by "NASTRAN". The mode shapes were then input to the doublet lattice portion of "NASTRAN" and used to calculate the aerodynamic influence coefficients (AICs) at fifteen reduced frequencies (see figure 4). The pade approximate curve fitting routine "QUEFIT" used the AICs at the reduced frequencies to calculate the generalized force matrices (see figure 5).

The control law for the third test flight of DAST ARW-1 was obtained from NASA Langley and is shown in figure 6. The portion of the control law used for the aileron mode was

$$g(s) = (1256.6)^2 / (s^2 + 502.7s + (1256.6)^2)$$

Therefore, the aileron mode had a natural frequency of 1256.6 hertz and a damping factor of 0.2. The remaining terms of the control law were put into matrices by the program "CONTRL".

The input file documentation needed to use the computer program "SAFSS" is presented in appendix B and a listing of the program is in appendix C. A sample input file for the DAST ARW-1 symmetric, .825 mach number, 15,000 feet altitude case is presented in appendix D. The output for the sample case is contained in appendix E.

CHAPTER 7

FLIGHT TEST DATA

Data from the third test flight of the DAST ARW-1 test vehicle was collected by the NASA Dryden Flight Test Research Center. The DAST was launched from a B-52 aircraft and remotely piloted to an altitude of 15,000 ft. Testing was performed at the following mach numbers; 0.70, 0.75, 0.775, 0.80 and 0.825.

The wing was vibrationally excited at each mach number to determine the vibrational stability. Excitation of the wing was produced by oscillating the aileron in a continuous frequency sweep from 10 to 40 hertz. Excitation sweeps were performed with the flutter suppression system (FSS) on and/or off (depending on the predicted stability at the test point) for both symmetric and asymmetric cases.

The FSS used for the DAST ARW-1 is active aileron control which operates in the following manner. Electrical signals from four accelerometers (two located in the fuselage and one in each wing) are sent to a compensator. The compensator separates the symmetric, asymmetric, and rigid body motions then signals the actuators to hydraulically move the ailerons. A time history of the accelerometer signals is used to calculate the frequencies of vibration and damping factors.

Because of an error in the implementation of the control law, the FSS was operated at one-half of the designed gain. This error caused test data for a gain factor

of one-half to be compared with predictions for a gain factor of one. As a result, the DAST ARW-1 with the FSS on entered a flutter region near mach 0.825 at 15,000 ft. and was lost.

CHAPTER 8

RESULTS

The natural frequencies for the symmetric case of DAST ARW-1 obtained from the program "NASTRAN" and from a ground vibrations test (GVT), are presented in Table 1. For the frequency range of interest (10-40 hertz), the predicted and actual frequencies agree to within 0.5 hertz. The first wing bending mode is of special importance because the aircraft fluttered in that mode. "NASTRAN" predicted the first bending mode to have a natural frequency of 9.1 hertz. The actual value was 9.6 hertz. The mode shapes and natural frequency were used to calculate the generalized force matrices therefore a 5% error could be considered large.

The data taken at mach 0.755 is believed to be unreliable because the wing showed uninitiated oscillations, possible due to atmospheric turbulence. The FSS (flutter suppression system) was left on for velocities of mach 0.755 and above. The FSS off data for mach 0.755 and above was calculated from FSS on information. Due to an error in the implementation of the control law, the FSS on condition was operating at one-half the desired gain ($K=.5$) for the test flight.

Table 2 shows the relationship between the predicted and experimental vibrational frequencies with the FSS off and Table 3 shows the relationship with the FSS on. The average error in frequency for the FSS off condition is 5% while the error for the FSS on condition is 8%.

The FSS increased the vibrational frequency from 13.91 hertz to 19.93 hertz. The analysis predicted the effect of the FSS quite well as an increase from 14.54 to 21.58 hertz.

A graph of root locus versus mach number for the 15,000 ft. altitude case for the first wing bending mode is shown in Figure 7. Three gain factors are plotted: full gain ($K=1$, the designed gain factor), half gain ($K=.5$, the actual FSS on gain) and no gain ($K=0$, the FSS off gain). The root locus plot is interpreted by noting that as the real term approaches the imaginary axis from the negative real side, the system becomes less stable. As the imaginary axis is crossed from the negative real to the positive real, the system goes from stable (no flutter) to unstable (flutter). The experimental results are shown to be consistently less damped and of a lower frequency than the predicted values. Trends seem to be predicted well, however more data is needed to draw any conclusions.

The predictions presented here are not the outcome of a single analysis, but rely on finite element, unsteady aerodynamics and vibrational analysis which tend to reduce the accuracy. The small difference which resulted can be caused by the inaccuracy (5%) of the finite element analysis alone.

CHAPTER 8

CONCLUSIONS

A method for analysis of an active aileron control flutter suppression system has been explained and compared with flight data. The method was shown to produce reasonable results but relies heavily on finite element and unsteady aerodynamic analysis. The ability of the finite element routine to match the mode shapes and natural frequencies of the ground vibration test will have a large affect on the accuracy of the flutter analysis.

Future work in this area will move toward digital instead of analog control systems. Digital systems will reduce space and weight requirements as well as make possible the use of dynamic control laws.

APPENDIX A

TABLES AND FIGURES

TABLE 1

NATURAL FREQUENCIES OF VIBRATION MODES PREDICTED BY NASTRAN
AND MEASURED DURING GROUND VIBRATION TEST

| Mode | frequency (hertz) | |
|------------------------|-------------------|------|
| | NASTRAN | GVT |
| First wing bending | 9.1 | 9.6 |
| First fuselage bending | 16.5 | 16.2 |
| Wing bending-torsion | 29.6 | 29.1 |

TABLE 2

VIBRATIONAL FREQUENCIES OF FIRST WING BENDING MODE
PREDICTED BY SAFSS AND OBTAINED FROM FLIGHT TESTS
FOR FSS OFF AT 15000 FT.

| Mach Number | Frequency (hertz) | |
|-------------|-------------------|-------------|
| | SAFSS | Flight Test |
| .75 | 13.24 | 12.25 |
| .80 | 15.54 | 13.91 |

TABLE 3
VIBRATIONAL FREQUENCY OF FIRST WING BENDING MODE
PREDICTED BY SAFSS AND OBTAINED FROM FLIGHT TEST
FOR FSS ON AT 15000 FT.

| Mach Number | Frequency (hertz) | |
|-------------|-------------------|-------------|
| | SAFSS | Flight Test |
| .80 | 21.58 | 19.93 |
| .825 | 21.71 | 20. |

Wing Span: 14.5 ft.

Airfoil: Supercritical

Aspect Ratio: 6.8




Figure 1. DAST ARW-1 planform




Figure 2. Flow Diagram of Program "SAFSS"




Figure 3. Flow Diagram of Main Subroutine of "SAFSS"




Figure 4. Block Diagram of Computer Programs Part 1





Figure 5. Block Diagram of Computer Programs Part 2

$$G(s) = \frac{(738)(2250) s (s^2 + 76.78s + (295.3)^2) (s^2 + 120s + (306)^2) (s^2 + 100s + (71)^2)}{(s + 2) (s + 295.3)^2 (s + 1500)^2 (s^2 + 240s + (342)^2) (s^2 + 100s + (58)^2) (s^2 + 100s + (112)^2)}$$

$$\frac{(s^2 + 100s + (168)^2) (295.3)^2 (1256.6)^2}{(s^2 + 76.78s + (295.3)^2) (s^2 + 589.4s + (439.8)^2) (s^2 + 502.7s + (1256.6)^2)}$$

Figure 6. Control Law for DAST A/V-1 Flight Test 3.

ORIGINAL PAGE IS
OF POOR QUALITY



APPENDIX B

This appendix contains a description of the input file for the computer program "SAFSS" (Stability Analysis of Flutter Suppression System). This program is designed to use the output of an aerodynamic influence coefficient curve fitting routine has outlined by Edwards in "Applications of Laplace Transform Methods to Airfoil Motion and Stability Calculations".

The input information includes the aerodynamics, the control law, and information about each mode, such generalized mass, frequency of oscillation in still air and physical information about the wing. The input is grouped into four blocks. The first block contains information about the analysis options and the size of the problem. The second has all the information about the control law. The third block contains all the aerodynamic matrices and mach number. The last block contains the wing vibration and mode shape information.

The term "card" means that all the information is contained on one card. The term "card set" will refer to a group of cards that contain the stated information. Card sets usually contain matrices. Matrices will be read in by rows (first row, second row etc.). The last value in a row of a matrix will be the last value read from that card. As an example, a ten by ten matrix to be input with only eight values read from each card, will need two cards for each row. The first card for each row will contain eight values with the second card containing the

last two.

| Variable Name | Column # | Format |
|---------------|----------|--------|
|---------------|----------|--------|

Description

CARD BLOCK 1 *****

CARD 1:-----

| | | |
|-----------------|------|-----|
| <u>TITLE(6)</u> | 1-46 | 6A8 |
|-----------------|------|-----|

The title and/or description desired on the data output and the root locus plot. The time and date will be supplied by the computer.

CARD 2:-----

| | | |
|--------------|-----|----|
| <u>NCASE</u> | 1-5 | I5 |
|--------------|-----|----|

The number of different altitudes that calculations are to be performed at.

| | | |
|-------------|------|----|
| <u>MODE</u> | 1-10 | I5 |
|-------------|------|----|

The number of vibration modes being used for the calculations. Must include the aileron mode.

| | | |
|---------------|-------|----|
| <u>MALERN</u> | 11-15 | I5 |
|---------------|-------|----|

The number of the vibration mode that contains the aileron mode. Usually the first or the last.

| | | |
|---------------|-------|----|
| <u>NGAINI</u> | 16-20 | I5 |
|---------------|-------|----|

The type of arithmetic progression desired for the gain factor, (1=linear,2=geometric).

Example: linear (0.,.25,.5,.75,1.0,1.25,1.5)

geometric (0.,.25,.5,1.0,2.0,4.0,8.0)

NGAINS 21-25 15

The number of gain factors to be analyzed including zero. In the example above, both linear and geometric have 7 gain factors.

GAINUP 26-35 F10.6

The desired value of the first gain factor after the pole (0.0).

Both the linear and geometric series in the above example have a value of .25.

IEGVEC 36-40 15

If the eigenvectors are to be printed, use the number "1". If any other number is found the eigenvectors will not be printed.

CLEN 41-50 F10.6

The span of the wing. It is used in the doublet lattice routine as the reference length to calculate the reduced frequency.

IPLT 51-55 15

If a root locus plot is desired, set equal to "1". If any other number is used, no plot will be made.

YMAX 56-65 F10.6

The maximum frequency (rad/sec) that is of interest. This value is used in plotting only, and does not effect the calculations.

CARD SET 3:-----

ALT(I) 1-80 8F10.6

This card(s) contains the altitudes to be used in the calculations. The maximum number of altitudes that can fit on one card is 8. If more than 8 altitudes are desired additional cards must be used.

CARD BLOCK 2 *****

This set of cards is obtained from the "Contrl" program as output. The entire block of cards is produced and order ready to be inserted into this data card deck.

CARD 4:-----

NCONTR 1-5 15

The size of the control matrix.

CARD SET 5:-----

AC(I.J) 1-80 4E20.13

This set of cards contains the "A" matrix of the control law. It is a square matrix with dimensions $N \times N$, wherein the order of the control matrix (does not include the terms used as the aileron mode).

CARD SET 6:-----

GC(I.1) 1-80 4E20.13

This set of cards contains the "G" matrix of the control law. It is a row matrix with $1 \times N$ dimensions, where N

is the order of the control matrix.

CARD SET 7:-----

HC(1.J)

1-80

4E20.13

This set of cards contains the "H" matrix of the control law. It is a column matrix with Nx1 dimensions, where N is the order of the control matrix.

CARD BLOCK 3:*****

This block of cards contains the P1', P2', P3', and R0' matrices as described by Edwards (ref. 1, 2, 3 and 4). This block of cards is designed to be used as a unit. There is no need to separate the information in this block at any time.

CARD 8:-----

MACH

1-10

F10.6

The mach number at which the calculations of the unsteady aerodynamics were performed at are included here. The unsteady aerodynamic data is only valid for one Mach number.

CARD 9:-----

ISYM

1-5

L5

This states whether the analysis is for a symmetric or asymmetric case, where "T" is for the symmetric and "F" is for the asymmetric case. These parameters have no effect on the problem, but does label the type of problem being solved.

CARD SET:-----

PI(K,L) 1-80 4E20.13

This set of cards contain the P_1' matrix. This matrix is square of dimension $M \times M$, where M is the number of mode shapes. One card is needed for every 8 elements in a row and there are M rows.

CARD SET 11:-----

P2(K,L) 1-80 4E20.13

Same as card set 10 except that it is the P_2' matrix

CARD SET 12:-----

P3(K,L) 1-80 4E20.13

Same as card set 10 except that it is the P_3' matrix.

CARD SET 13:-----

RO(K,L) 1-80 4E20.13

Same as card set 10 except that it is the R_0' matrix.

CARD BLOCK 4 *****

This card block contains the physical characteristics of the wing and should remain the same throughout the analysis.

CARD SET 14:-----

OMEGA(I) 1-80 8F10.6

This card contains the vibrational frequency of each mode shape. It is important that the order of the mode shapes is the same as the order for the doublet lattice routine. The frequency

for the aileron mode is obtained from the 2'nd order term of the control law and was not input in the "Control" program.

CARD SET 15:-----

ZETA(I) 1-80 8F10.6

This card contains the damping factor for each vibration mode. The modal damping term for the aileron mode is obtained from the 2'nd order term of the control law that was not input into the "Control" program. The modal damping term for the other modes were hard to obtain therefore, a small value of approximately .005, was assumed.

CARD SET 16:-----

GMASS(I) 1-80 8F10.6

This card contains the generalized mass terms for each mode. The value for the generalized mass term of the aileron has a value of 1.0000. If the user does not set the aileron term to 1.0000, the program will do so.

CARD SET 17:-----

DEFLECT(I) 1-80 8F10.6

The deflection of the wing at the accelerometer location for each mode shape. The deflection for the aileron mode should be zero.

CARD SET 18:-----

XMD

1-10

F10.6

The mass of the aileron in consistent units. If the problem has been done in units of inches, seconds, and pounds (as is usually the case) the mass should be of such units as to be consistent with the rest of the problem. The consistent units for the above example are the mass of the aileron in slugs divided by 12 in/ft. The program does not do this type of conversion so that other system of units can be used.

CONVFT

31-40

F10.6

This card contains the conversion factor for the units of the input and output of the control law used in this analysis. If the control law input is in g's (gravities) and the analysis is in inches and seconds a conversion must be made. Likewise, the output of the control law output may be in degrees and the mode shape deflection may be one inch. For this example, the input portion of the conversion is $(1g)/(32.2 \text{ ft/sec}^2 * 12 \text{ in/ft})$. The output portion would be $(1 \text{ degree})/(\text{the angle due to the one inch deflection})$. The proper conversion is obtained by multiplying the two terms.

CARD SET 19:-----

The information below is required for each mode shape. The aileron mode will have a hinge line deflection of zero. Each card contains the information for one mode.

PHI(I)

1-10

F10.6

- The average deflection at leading edge of the aileron.

SIG(I)

21-22

F10.6

The average deflection at the trailing edge of the aileron.

APPENDIX C
LISTING OF PROGRAM "SAFSS"

#DECK SAFSS

PROGRAM MAIN (INPUT,OUTPUT,TAPE1=INPUT,TAPE6=OUTPUT)

C*****

C

C PROGRAM SAFSS (STABILITY ANALYSIS OF FLUTTER SUPPRESSION SYSTEM)

C

C*****

C

C THIS PROGRAM PUTS TOGETHER AND SOLVES THE MATRIX REPRESENTING THE
C WING MOTION AND THE CONTROL LAW.

C

C THE PROGRAM IS SETUP TO TAKE THE CONTROL LAW MATRICES, THE
C GENERALIZED FORCE MATRICES FOR A GIVEN MACH #,

C THE MODAL FREQUENCIES, THE GENERALIZED MASS AT EACH MODE, THE
C DEFLECTION AT THE ACCELEROMETER OF EACH MODE, THE AVERAGE DEFLECT-
C ION OF THE AILERON AT THE LEADING AND TRAILING EDGE FOR EACH MODE,
C AND THE MASS OF THE AILERON AND OUTPUT A ROOT LOCUS
C PLOT OF THE FREQUENCIES OF VIBRATION FOR THE ALTITUDES OF INTEREST.

C

C*****

C

C DESCRIPTION OF INPUT DATA

C

C*****

C

C TITLE = TITLE OF THE JOB
C NCASE = NUMBER OF ALTITUDES TO BE EVALUATED
C MODE = NUMBER OF VIBRATION MODE BEING USED
C MALERN = WHICH VIBRATION MODE IS THE AILERON DEFLECTION MODE
C IEGVEC = DO YOU WANT THE IEIGEN VECTORS PRINTED (0=NO)
C NGAINF = NUMBER OF GAIN FACTORS TO BE SOLVED INCLUDING ZERO
C NGAINT = TYPE OF GAIN FACTOR PROGRESSION USED
C (1=LINEAR, 2=GEOMETRIC)
C GAINUP = FIRST GAIN FACTOR TO BE USED AFTER ZERO
C ALT(I) = ALTITUDE OF THE I' TH ROOT LOCUS PLOT
C NCONTR = SIZE OF THE CONTROL MATRIX

??

C AC(I,J) = THE "A" MATRIX OF THE CONTROL LAW
 C GC(I,J) = THE "G" MATRIX OF THE CONTROL LAW
 C HC(I,I) = THE "H" MATRIX OF THE CONTROL LAW
 C P1(K,L) = THE S**2 TERM OF THE PADE APPROXIMANT OF THE LOAD
 C P2(K,L) = THE S TERM OF THE PADE APPROXIMANT OF THE LOAD
 C P3(K,L) = THE CONSTANT TERM OF THE PADE APPROXIMANT OF THE LOAD
 C RO(K,L) = THE EIGENVALUE TERM OF THE PADE APPROXIMANT TO THE LOAD
 C OMEGA(I) = FREQUENCIES OF THE CORRESPONDING VIBRATION MODE
 C ZETA(I) = DAMPING OF THE CORRESPONDING VIBRATION MODE
 C GMASS = GENERALIZED MASS OF THE CORRESPONDING VIBRATION MODE
 C DEFLECT = DEFLECTION AT THE ACCELEROMETER FOR EACH MODE
 C XMD = MASS OF THE AILERON
 C CONVFT = CONVERSION FACTOR BETWEEN CONTROL LAW UNITS AND THE
 C UNITS USED WITH THIS PROGRAM.
 C PHI(I) = AVERAGE DEFLECTION OF THE AILERON LEADING EDGE FOR
 C THE I'TH MODE
 C SIG(I) = AVERAGE DEFLECTION OF THE AILERON TRAILING EDGE FOR
 C THE I'TH MODE
 C

C*****

DIMENSION W1(11,11),W2(11,11),W3(11,11)
 DIMENSION P1(11,11),P2(11,11),P3(11,11),RO(11,11),VP3(11,11),
 1VRO(11,11),OMEGA2(11,11),GBM(11,11),B(11,11),VP1H2(11,11),
 2VP1(11,11),TITLE(8),OMEGA(11),ZETA(11),GMASS(11),A(48,48),WR(48),
 3WI(48),Z(11,11),Z3(48,48),INT(48),AC(15,15),AMTRX(33,33),
 4BMTRX(33,1),FMTRX(1,1),GMTRX(1,33),HMTRX(1,33),W4(33,33),
 5PHI(11),SIG(11),REACT(11),DEFLECT(11),ALT(20),
 .GC(15,1),HC(1,15),W5(1,11),W6(15,11),W7(11,15),W8(15,11),
 .W9(11,1),W10(1,15),W11(11,15),W12(15,15)
 READ 801,(TITLE(I),I=1,6)
 CALL DATE(TITLE(7))
 CALL TIME(TITLE(8))
 PRINT 901,TITLE
 READ 802, NCASE, MODE, MALERN, NGAINT, NGAINS, GAINUP, IEGVEC, CLEN,
 IPLT, YMAX
 READ 804, (ALT(I), I=1, NCASE)


```

      READ B02, NCONTR
      MSIZE=MODE*3+NCONTR
      MODE3=MODE*3
      CALL PADJR (NCASE,MODE,MODE3,MSIZE,MALERN,CLEN,W1,W2,W3,
        .P1,P2,P3,RO,VP3,VRO,OMEGA2,QBM,B,VP1H2,VP1,OMEGA,ZETA,QMASS,
        .A,WR,WI,Z,Z3,IEGVEC,INT,AC,NCONTR,AMTRX,BMTRX,FMTRX,GMTRX,HMTRX,
        .W4,PHI,SIG,REACT,DEFLECT,ALT,GC,HC,W5,W6,W7,W8,W9,W10,W11,W12,
        .NGAINT,NGAINS,GAINUP,IPLT,YMAX)
      B01 FORMAT(8A8)
      B04 FORMAT(8F10.6)
      B02 FORMAT(5I5,F10.6,I5,F10.6,I5,F10.6)
      B01 FORMAT(1H1,10X,8A8)
      END
      SUBROUTINE PADJR(NCASE,MODE,MODE3,MSIZE,MALERN,CLEN,W1,W2,
        .W3,P1,P2,P3,RO,VP3,VRO,OMEGA2,QBM,B,VP1H2,VP1,OMEGA,ZETA,
        .QMASS,A,WR,WI,Z,Z3,IEGVEC,INT,AC,NCONTR,AMTRX,BMTRX,FMTRX,GMTRX,
        .HMTRX,W4,PHI,SIG,REACT,DEFLECT,ALT,GC,HC,W5,W6,W7,W8,W9,W10,
        .W11,W12,NGAINT,NGAINS,GAINUP,IPLT,YMAX)
C *****
C
C      SUBROUTINE PADJR
C
C *****
C
C      THIS PROGRAM RESIZES THE ARRAYS TO FIT THE PROBLEM THEN READS
C      THE INPUT INFORMATION AND THEN CREATES AND SOLVES THE STATE SPACE
C      MATRIX.
C *****
      LOGICAL ISYM
      REAL MACH
      DIMENSION PHI(MODE),SIG(MODE),REACT(MODE),DEFLECT(MODE),
        .W1(MODE,MODE),W2(MODE,MODE),W3(MODE,MODE),
        .P1(MODE,MODE),P2(MODE,MODE),P3(MODE,MODE),RO(MODE,MODE),
        .VP3(MODE,MODE),VRO(MODE,MODE),OMEGA2(MODE,MODE),QBM(MODE,MODE),
        .B(MODE,MODE),VP1H2(MODE,MODE),VP1(MODE,MODE),

```

```

.OMEGA(MODE), ZETA(MODE),
.GMASS(MODE), A(MSIZE,MSIZE),WR(MSIZE),WI(MSIZE),Z(MODE,MODE),
.INT(MSIZE),Z3(MSIZE,MSIZE),ALT(NCASE),AC(NCONTR,NCONTR),
.ANTRX(MODE3,MODE3),BMTRX(MODE3,1),FMTRX(1,1),GMTRX(1,MODE3),
.HMTRX(1,MODE3),W4(MODE3,MODE3),GC(NCONTR,1),HC(1,NCONTR),
.W5(1,MODE),W6(NCONTR,MODE),W7(MODE,NCONTR),W8(NCONTR,MODE),
.W9(MODE,1),W10(1,NCONTR),W11(MODE,NCONTR),W12(NCONTR,NCONTR)
C*****
C  READ MATRICES REPRESENTING CONTROL LAW (FROM PROGRAM "CONTROL")
C*****
      DO 11 I=1,NCONTR
11  READ 801,(AC(I,J),J=1,NCONTR)
      READ 801,(GC(IR,1),IR=1,NCONTR)
      READ 801,(HC(1,IC),IC=1,NCONTR)
C*****
C  READ MACH NUMBER. READ (T/F) WHETHER SYMMETRIC OR ASYMMETRIC
C  READ PADE APPROXIMATE MATRICES FOR UNSTEADY AERODYNAMICS. MATRICES
C  ARE P1',P2',P3',R0'.
C*****
      READ 802,MACH
      READ 803,ISYM
      DO 12 IR=1,MODE
      READ 801,(P1(IR,IC),IC=1,MODE)
12  CONTINUE
      DO 13 IR=1,MODE
      READ 801,(P2(IR,IC),IC=1,MODE)
13  CONTINUE
      DO 14 IR=1,MODE
      READ 801,(P3(IR,IC),IC=1,MODE)
14  CONTINUE
      DO 15 IR=1,MODE
      READ 801,(R0(IR,IC),IC=1,MODE)
15  CONTINUE
C*****
C  READ NATURAL FREQUENCIES OF WING VIBRATION, MODAL DAMPING TERMS,
C  GENERALIZED MASS TERMS, AND THE DEFLECTION OF WING AT THE

```

```

C  ACCELEROMETER LOCATION.
C *****
  READ B02,(OMEGA(I),I=1,MODE)
  READ B02,(ZETA(I),I=1,MODE)
  READ B02,(GMASS(I),I=1,MODE)
  READ B02,(DEFLECT(I),I=1,MODE)
C *****
C  READ THE MASS OF THE AILERON, THE CONVERSION FACTOR BETWEEN
C  THE UNITS OF THE CONTROL LAW AND THE UNITS OF THIS ANALYSIS.
C *****
  READ B02,XMD,CONVFT
C *****
C  READ THE MODAL AVERAGE DEFLECTION AT THE LEADING EDGE OF
C  THE AILERON AND THE AVERAGE MODAL DEFLECTION AT THE TRAILING EDGE
C  OF THE AILERON FOR EACH MODE.
C *****
  DO 16 I=1,MODE
    16 READ B02,PHI(I),SIG(I)
C *****
C  END OF INPUT REGION
C *****
C  PRINT INFORMATION FOR LISTING
C *****
  PRINT 904,MACH,MODE,NCONTR,CLEN
  PRINT 906,(ALT(I),I=1,NCASE)
  PRINT 901,(OMEGA(I),I=1,MODE)
  PRINT 902,(ZETA(I),I=1,MODE)
  PRINT 903,(GMASS(I),I=1,MODE)
  PRINT 908
  DO 17 IR=1,MODE
    PRINT 907,(P1(IR,IC),IC=1,MODE)
  17 CONTINUE
  PRINT 909
  DO 18 IR=1,MODE
    PRINT 907,(P2(IR,IC),IC=1,MODE)
  18 CONTINUE

```

```

      PRINT 910
      DO 19 IR=1,MODE
      PRINT 907,(P3(IR,IC),IC=1,MODE)
19  CONTINUE
      PRINT 911
      DO 20 IR=1,MODE
      PRINT 907,(R0(IR,IC),IC=1,MODE)
20  CONTINUE
      PRINT 912
C*****
C  START PUTTING TOGETHER THE MATRIX FOR SOLUTION
C*****
C  CALCULATE EFFECT OF THE AILERON MODE ON OTHER MODES
C  (NONDIAGONAL TERMS OF THE MASS MATRIX)
C*****
      SI=SIG(MALERN)-PHI(MALERN)
      DO 21 I=1,MODE
21  REACT(I)=-XMD*SI*(PHI(I)/2+(SIG(I)-PHI(I))/3)
      REACT(MALERN)=1.
      GMASS(MALERN)=1.
C*****          INITIALIZE PLOTTER *****
      IF (IPLT.EQ.1) CALL INITPLT
C*****
C  START OF LOOP FOR EACH ALTITUDE CALCULATIONS
C*****
      DO 500 ICASE=1,NCASE
C*****          PLOT AXIS *****
      IF (IPLT.EQ.1) CALL AXISPLT(ALT(NCASE),MACH,YMAX,YMIN,
        .XMAX,XMIN,SCALE,ISYM,TITLE)
C*****
C  CALCULATE DYNAMIC PRESSURE AND AIR SPEED
C*****
      CALL QBARC (MACH,ALT(ICASE),U,QBAR,INFLG)
      PRINT 921
      PRINT 922, MACH,ALT(ICASE),QBAR,U
C*****

```

C CALCULATE THE P3 AND R0 MATRICES FORM THE P3' AND R0' MATRICES BY
 C MULTIPLYING BY THE VELOCITY OVER THE SEMI-SPAN. CALCULATE THE P1
 C MATRIX BY DIVIDING THE P1' MATRIX BY THE VELOCITY OVER THE
 C SEMI-SPAN.

C*****

UB=U/(CLEN/2.)
 CALL ARITH (UB,P3,0.,P3,VP3,MODE,MODE)
 CALL ARITH (UB,R0,0.,R0,VRO,MODF,MODE)
 UB=1./UB
 CALL ARITH (UB,P1,0.,P1,VP1,MODE,MODE)

C*****

C CONSTRUCT THE K/M, B/M AND G/M MATRICES.

C*****

DUM1=OMEGA(MALERN)**2
 DUM2=2.*OMEGA(MALERN)*ZETA(MALERN)
 DO 31 IR=1,MODE
 DO 30 IC=1,MODE
 OMEGA2(IR,IC)=0.
 B(IR,IC)=0.
 GBM(IR,IC)=0.
 30 CONTINUE
 OMEGA2(IR,IR)=OMEGA(IR)**2
 B(IR,IR)=2.*OMEGA(IR)*ZETA(IR)
 IF (IR.NE.MALERN) GBM(IR,IR)=GBAR/GMASS(IR)
 IF (IR.NE.MALERN) OMEGA2(IR,MALERN)=DUM1*REACT(IR)/GMASS(IR)
 IF (IR.NE.MALERN) B(IR,MALERN)=DUM2*REACT(IR)/GMASS(IR)
 31 CONTINUE

C*****

C CONSTRUCT: -P3 + P1*K/M

C -P2 + P1*B/M

C R0 - P1*G/M

C*****

CALL MULT(VP1,OMEGA2,W1,MODE)
 CALL ARITH(1.,VP3,-1.,W1,W1,MODE,MODE)
 CALL MULT(VP1,B,W2,MODE)
 CALL ARITH(1.,P2,-1.,W2,W2,MODF,MODE)

```

      CALL MULT(VP1,QBM,W3,MODE)
      CALL ARITH(-1.,VRD,1.,W3,W3,MODE,MODE)
      XK=0.
      IDUM1=NGAINS+1
      DO 400 KK=1,IDUM1
C*****
C  PLACE SMALL MATRICES INTO ONE LARGE MATRIX
C*****
      DO 32 IR=1,MSIZE
      DO 32 IC=1,MSIZE
32  A(IR,IC)=0.
      DO 33 IR=1,MODE
      A(2*IR-1+MODE,2*IR+MODE)=1.
      DO 33 IC=1,MODE
      A(2*IR+MODE,2*IC-1+MODE)=-OMEGA2(IR,IC)
      A(2*IR+MODE,2*IC+MODE)=-B(IR,IC)
      A(2*IR+MODE,IC)=QBM(IR,IC)
      A(IR,IC)=W3(IR,IC)
      A(IR,2*IC-1+MODE)=W1(IR,IC)
      A(IR,2*IC+MODE)=W2(IR,IC)
33  CONTINUE
C*****
C  ADD ADDITIONAL TERMS TO THE LARGE MATRIX THAT ARE CAUSED BY THE
C  ADDITION OF THE FLUTTER SUPPRESSION SYSTEM.
C*****
      CALL FSS(A,OMEGA2,B,QBM,MODE,MSIZE,NCONTR,MALERN,
      .DEFLECT,REACT,GMASS,VP1,AC,GC,HC,W5,W6,W7,W8,W9,
      .W10,W11,W12,XK,CONVFT)
C*****
C  END OF MATRIX CONSTRUCTION, NOW GET THE EIGENVALUES
C*****
      CALL ELMHES (MSIZE,MSIZE,1,MSIZE,A,INT)
      CALL ELTRAN (MSIZE,MSIZE,1,MSIZE,A,INT,Z3)
      CALL HQR2(MSIZE,MSIZE,1,MSIZE,A,IR,WI,Z3,IERR,0)
C***** IF ZEROS WERE CALCULATED GO TO ZERO PLOTTER SECTION *****
      IF (XK.EQ.1000000.) GO TO 42

```

```

PRINT 931,XK
PRINT 932,IERR
C***** CALCULATE FREQUENCIES AND DAMPING *****
DO 41 IE=1,MSIZE
WNZ=WR(IE)*WR(IE)+WI(IE)*WI(IE)
WN=SQRT(WNZ)
ZTA =-WR(IE)/WN
CYCLES=WN*.16034
PRINT 933, WR(IE), WI(IE), WN, CYCLES, ZTA
41 CONTINUE
C*****
C PLOT RESULTS ON ROOT LOCUS PLOT.
C*****
IF (IPLT.EQ.1) CALL POINT(MSIZE,WR,WI,SCALE,KK,XK,YMAX,YMIN,
,XMAX,XMIN)
C***** CHANGE THE GAIN FACTOR *****
IF (NGAINT.EQ.1) XK=XK+GAINUP
IF (NGAINT.EQ.2) XK=GAINUP*2*(KK-1)
IF (NGAINS.EQ.KK) XK=1000000.
GO TO 43
C*****
C PLOT AND LIST THE ZEROS OF THE MATRIX
C*****
42 PRINT 951
PRINT 952,(WR(I),WI(I),I=1,MSIZE)
IF (IPLT.EQ.1) CALL ZEROPLT(MSIZE,WR,WI,SCALE,YMAX,YMIN,
,XMAX,XMIN,NGAINS)
C*****
C UNPACK THE EIGENVECTOR MATRIX (Z) PER EISPACK GUIDE
C AND LIST.
C*****
43 IF (IEGVEC.EQ.0) GO TO 400
PRINT 941
L=1
111 CONTINUE
IF (MSIZE.LE.10*L) GO TO 110

```

```

      L=L+1
      GO TO 111
110 CONTINUE
      LL=MSIZE-10*(L-1)
      LLL=1
113 CONTINUE
      I=9
      IF (LLL.EQ.L) I=LL
      PRINT 968
      II=(LLL-1)*10+1
      III=II+I
      PRINT 942,((WR(J),WI(J)),J=II,III)
      PRINT 968
      DO 51 J=1,MSIZE
      PRINT 942,(Z3(J,K),K=II,III)
51 CONTINUE
      LLL=LLL+1
      IF (LLL.GT.L) GO TO 115
      GO TO 113
115 CONTINUE
C*****
C  ENDS LOOP. GO BACK AND CALCULATE NEXT GAIN FACTOR.
C*****
      400 CONTINUE
C*****
C  ENDS LOOP, GO BACK FOR NEXT ALTITUDE
C*****
500 CONTINUE
801 FORMAT(4E20.13)
802 FORMAT(8F10.6)
803 FORMAT(L5)
904 FORMAT(/,15X,"MACH -",FG.3,10X,I1," VIBRATION MODES"
      ,/,10X,I2,"TH ORDER CONTROL LAW",10X,"CHARACTERISTIC LENGTH-",
      ,F7.3)
906 FORMAT(/10X,"ALTITUDES TO BE EVALUATED-----",/2(/10X(1X,G12.6)))
901 FORMAT(/10X,"MODAL FREQUENCIES-----",/10(1X,G12.6))

```



```

902 FORMAT(/10X,"MODAL DAMPING-----",/10(1X,G12.6))
903 FORMAT(/10X,"GENERALIZED MASSES-----",/10(1X,G12.6))
908 FORMAT(/10X,"P1 MATRIX-----"/)
907 FORMAT(10(1X,G12.6))
909 FORMAT(/10X,"P2 MATRIX-----"/)
910 FORMAT(/10X,"P3 MATRIX-----"/)
911 FORMAT(/10X,"R0 MATRIX-----"/)
912 FORMAT(10X," - END OF INPUT DATA _")
921 FORMAT(1H1,5X,10(" NEW CASE ")//)
922 FORMAT(10X,"MACH =",G16.6/10X,"ALT  =",G16.6/10X,
."QBAR =",G16.6/10X,"VTRUE=",G16.6)
931 FORMAT(/20X,"THE GAIN FACTOR =",F6.3,/)
932 FORMAT(/10X,"EIGENVALUES COMPUTED, ERROR CODE=",I4,/,12X,
."REAL PART",8X,"IMAGINARY PART",2(9X,"FREQUENCY",3X),
.4X,"DAMPING FACTOR",/5X,3(8X,"RAD/SEC",5X),8X,
."CYCLE/SEC",/)
933 FORMAT(5X,4(F15.2,5X),F15.4)
941 FORMAT(///10X,"THE EIGENVECTORS ARE",/)
968 FORMAT(//)
942 FORMAT(10E13.5)
951 FORMAT(///10X,"THE ZEROS ARE LOCATED AT:",/12X,"REAL PART",
.8X,"IMAGINARY PART",/5X,2(8X,"RAD/SEC",5X),/)
952 FORMAT(2(5X,F15.2))
      RETURN
      END
      SUBROUTINE CROSS (A,B,C,I,J,K)
C*****
C
C      SUBROUTINE CROSS
C
C*****
C
C      THIS PROGRAM MULTIPLES MATRIX "A" BY MATRIX "B". MATRIX "A" IS
C      NECESSARILY AN I BY J MATRIX AND MATRIX "B" IS NECESSARILY AN
C      J BY K MATRIX. THE RESULT OF THE MULTIPLICATION IS MATRIX "C" (I BY K)
C      * NOTE: IF THE ARRAY "C" IS THE SAME ARRAY AS "A" OR "B" THE PROBLEM

```

```

C          IS PROBABLE SCREWED UP
C
C *****
C      DIMENSION A(I,J),B(J,K),C(I,K)
C      DO 25 L=1,I
C      DO 25 N=1,K
C      C(L,N)=0.0
C      DO 25 M=1,J
C      C(L,N)=C(L,N)+A(L,M)*B(M,N)
C 25 CONTINUE
C      RETURN
C      END
C      SUBROUTINE INITPLT
C *****
C
C      SUBROUTINE INITPLT  (INITIALIZE PLOTTER)
C
C *****
C
C      THE ENTIRE 5 LINES OF THE PROGRAM IS SUPPOSED TO INITIALIZE THE PLOTTER.
C      THESE INSTRUCTIONS ARE FOR A CALCOMP PLOTTER. IF YOU ARE USING
C      ANOTHER TYPE OF PLOTTER YOU MAY NEED TO CHANGE THESE INSTRUCTIONS OR
C      GET RID OF THEM ALL TOGETHER. THE OTHER PROGRAMS THAT DEAL WITH
C      PLOTTING INSTRUCTIONS ARE AXISPLT, POINTS, AND ZEROPLT.
C
C *****
C      CALL PLOTS(0,0,4)
C      CALL FACTOR(.7874)
C      RETURN
C      END
C      SUBROUTINE AXISPLT(ALT,MACH,YMAX,YMIN,XMAX,XMIN,SCALE,ISYM,TITLE)
C *****
C
C      SUBROUTINE AXISPLT  (AXIS PLOT)
C
C *****

```

```

C
C THIS PROGRAM DRAWS THE AXISES AND THE INFORMATION NECESSARY TO
C DESCRIBE WHAT THE PLOT IS OF (MACH NUMBER, ALTITUDE, TITLE...).
C OH, BY THE WAY THIS IS FOR A ROOT LOCUS PLOT.
C THESE PROGRAM IS WRITEN WITH CALCOMP PLOTTER INSTRUCTIONS SO
C TAKE IT OR WRITE YOUR OWN. IF DO NEED TO CHANGE IT THE OTHER
C SUBROUTINES THAT ALSO USE PLOTTER INSTRUCTIONS ARE INITPLT,
C POINT, ZEROPLT.
C
C*****
      INTEGER TITLE(8)
      LOGICAL ISYM
      SCL=YMAX/11.
      NEXP=0
      IF (SCL.LT.1.) GO TO 30
10  IF (SCL.LE.10.) GO TO 50
      SCL=SCL/10.
      NEXP=NEXP+1
      GO TO 10
30  IF (SCL.GT..1) GO TO 50
      SCL=SCL*10.
      NEXP=NEXP-1
      GO TO 30
50  IF (SCL.GT.5.) SCALE=10.*10.**NEXP
      IF (SCL.LE.5..AND.SCL.GT.2.) SCALE=5.*10.**NEXP
      IF (SCL.LE.2.) SCALE=2.*10.**NEXP
      IF (SCL.GT.2.AND.SCL.LE.2.5.AND.NEXP.GE.1) SCALE=2.5*10.**NEXP
      XMIN=-SCALE*6.
      XMAX=SCALE*2
      YMIN=0.
      CALL PLOT(0.,0.,3)
      CALL PLOT(10.795,0.,-3)
      IF (ICASE.EQ.1) CALL PLOT(6.,1.,-3)
      CALL PLOT(0.,11.,2)
      CALL AXIS(2.,0.,24HIMAGINARY AXIS (RAD/SEC),-24,11.,90.,0.,SCALE)
      CALL AXIS(-6.,0.,19HREAL AXIS (RAD/SEC),-19,8.,0.,XMIN,SCALE)

```

```

CALL SYMBOL(-6.,-1.25,.10,12HGAIN FACTORS,0.,11)
CALL SYMBOL(-6.,-1.5,.10,7HSYMBOLS,0.,7)
CALL SYMBOL(-6.,12.,.14,11PALITUDE = ,0.,11)
CALL NUMBER(999.,999.,.14,ALT,0.,0)
CALL SYMBOL(999.,999.,.14,12H MACH = ,0.,12)
CALL NUMBER(999.,999.,.14,MACH,0.,3)
IF (ISYM) CALL SYMBOL(999.,999.,.14,14H SYMMETRIC,0.,14)
IF (.NOT.ISYM) CALL SYMBOL(999.,999.,.14,15H ASYMMETRIC,0.,15)
CALL SYMBOL(-6.,11.6,.10,TITLE,0.,80)
RETURN
END

```

```

SUBROUTINE POINT(MSIZE,WR,WI,SCALE,KK,XK,YMAX,YMIN,XMAX,XMIN)

```

```

C*****

```

```

C

```

```

PROGRAM POINT (DRAWS POINTS ON THE PLOT)

```

```

C

```

```

C*****

```

```

C

```

```

THIS PROGRAMS TAKES THE EIGENVALUES AND PLOTES THEM IF THEM ARE
WITHIN THE AXIS OF THE PLOT. EACH GAIN FACTOR HAS A DIFFERENT
SYMBOL TO REPRESENT IT. "X" IS ALWAYS USED FOR THE POLES AND "Z"
IS SAVED FOR THE ZEROS WHICH ARE PLOTTED IN ANOTHER PROGRAM.
THE INSTRUCTIONS USED IN THIS PROGRAM ARE FOR A CALCOMP PLOTTER,
SO THEM MAY NEED TO BE CHANGFD. THE OTHER PROGRAMS THAT USE PLOTTER
INSTRUCTIONS ARE INITPLT, AXISPLT. AND ZEROPLT.

```

```

C

```

```

C*****

```

```

DIMENSION WR(MSIZE),WI(MSIZE)
IF (XK.EQ.0.) ISYM=4
DO 10 I=1,MSIZE
IF (WR(I).LT.XMIN.OR.WR(I).GT.XMAX.OR.
WI(I).LT.YMIN.OR.WI(I).GT.YMAX) GO TO 10
XN=WR(I)/SCALE
YN=WI(I)/SCALE
CALL SYMBOL(XN,YN,.14,ISYM,0.,1)

```

```

10 CONTINUE

```

```

PX=-4.5+KK*.6
CALL NUMBER(PX,-1.25,.1,XK,0.,2)
CALL SYMBOL(999.,999.,25,0.,-1)
PX=PX+.3
CALL SYMBOL(PX,-1.45,ISYMB,0.,-1)
IF (ISYMB.EQ.4) ISYMB=-1
ISYMB=ISYMB+1
IF (ISYMB.EQ.4) ISYMB=5
IF (ISYMB.EQ.8) ISYMB=9
RETURN
END
SUBROUTINE ZEROPLT(MSIZE,WR,WI,SCALE,YMAX,YMIN,XMAX,XMIN,KK)
C*****
C
C   PROGRAM ZEROPLT   (PLOTTER ZEROS)
C
C*****
C
C   THIS PROGRAM TAKES THE EIGENVALUES WHICH REPRESENT THE ZEROS OF
C   THE MATRIX AND PLOTTER THEM IF THEY ARE WITHIN THE BONDS OF THE
C   AXES. THE INSTRUCTIONS IN THIS PROGRAM ARE FOR A CALCOMP PLOTTER
C   AND MAY NEED TO BE CHANGED. THE OTHER ROUTINES THAT USE PLOTTER
C   COMMANDS ARE INITPLT, AXISPLT, AND POINT. THE ZEROS ARE REPRESENTED
C   BY A "Z" ON THE PLOT.
C
C*****
C   DIMENSION WR(MSIZE),WI(MSIZE)
C   ISYMB=8
C   DO 10 I=1,MSIZE
C     IF (WR(I).LT.XMIN.OR.WR(I).GT.XMAX.OR.
C       .WI(I).LT.YMIN.OR.WI(I).GT.YMAX) GO TO 10
C     XN=WR(I)/SCALE
C     YN=WI(I)/SCALE
C     CALL SYMBOL(XN,YN,.14,ISYMB,0.,-1)
10  CONTINUE
PX=-4.5+(KK+1.5)*.6

```

ORIGINAL PAGE IS
OF POOR QUALITY

```

CALL SYMBOL(PX,-1.20,24,0.,-1)
CALL SYMBOL(PX,-1.45,8,0.,-1)
RETURN
END
SUBROUTINE FSS(A,OMEGA2,B,QBM,MODE,MSIZE,NCONTR,MALERN,
.DEFLECT,REACT,GMASS,VP1,AC,GC,HC,W5,W6,W7,W8,W9,
.W10,W11,W12,XK,CONVFT)

```

```

C*****

```

```

C
C   PROGRAM FSS      (FLUTTER SUPPRESSION SYSTEM)
C

```

```

C*****

```

```

C
C   THIS PROGRAM ADDS THE ADDITIONAL TERMS TO THE MATRIX THAT A FLUTTER
C   SUPPRESSION SYSTEM CAUSES SUCH AS THE CONTROL LAW AND THE REACTION
C   OF THE MODES TO THE MOTION OF THE AILERON RESPONDING TO THE CONTROL
C   LAW.
C

```

```

C*****

```

```

      DIMENSION A(MSIZE,MSIZE),OMEGA2(MODE,MODE),B(MODE,MODE),
      .QBM(MODE,MODE),DEFLECT(MODE),REACT(MODE),GMASS(MODE),
      .VP1(MODE,MODE),AC(NCONTR,NCONTR),GC(NCONTR,1),HC(1,NCONTR),
      .W5(1,MODE),W6(NCONTR,MODE),W7(MODE,NCONTR),W8(NCONTR,MODE),
      .W9(MODE,1),W10(1,NCONTR),W11(MODE,NCONTR),W12(NCONTR,NCONTR)

```

```

      MODE3=MODE*3

```

```

      C=XK*OMEGA2(MALERN,MALERN)*CONVFT

```

```

      DO 11 L=1,MODE

```

```

        W5(1,L)=DEFLECT(L)

```

```

        W9(L,1)=REACT(L)/GMASS(L)

```

```

      11 CONTINUE

```

```

      DO 12 K=1,NCONTR

```

```

        W10(1,K)=C*HC(1,K)

```

```

      12 CONTINUE

```

```

C*****      CALCULATE THE G*D*Q/M MATRIX      *****

```

```

      CALL CROSS(GC,W5,W8,NCONTR,1,MODE)

```

```

      CALL CROSS(W6,QBM,W8,NCONTR,MODE,MODE)

```

```

DO 21 IR=1,NCONTR
DO 21 IC=1,MODE
A(IR+MODE3,IC)=WB(IR,IC)
21 CONTINUE
C***** CALCULATE THE -G*D*K/M MATRIX *****
CALL CROSS(W6,OMEGA2,W8,NCONTR,MODE,MODE)
DO 22 IR=1,NCONTR
DO 22 IC=1,MODE
A(IR+MODE3,2*IC-1+MODE)=-WB(IR,IC)
22 CONTINUE
C***** CALCULATE THE -G*D*B/M MATRIX *****
CALL CROSS(W6,B,W8,NCONTR,MODE,MODE)
DO 23 IR=1,NCONTR
DO 23 IC=1,MODE
A(IR+MODE3,2*IC+MODE)=-WB(IR,IC)
23 CONTINUE
C***** CLACULATE THE C*H/M MATRIX *****
CALL CROSS(W9,W10,W11,MODE,1,NCONTR)
DO 24 IR=1,MODE
DO 24 IC=1,NCONTR
A(2*IR+MODE,IC+MODE3)=W11(IR,IC)
24 CONTINUE
C***** CALCULATE THE A + G*D*C*H/M MATRIX *****
CALL CROSS(W6,W11,W12,NCONTR,MODE,NCONTR)
DO 25 IR=1,NCONTR
DO 25 IC=1,NCONTR
A(IR+MODE3,IC+MODE3)=AC(IR,IC)+W12(IR,IC)
25 CONTINUE
C***** CALCULATE THE P1+C*H/M MATRIX *****
CALL CROSS(VF1,W11,W7,MODE,MODE,NCONTR)
DO 26 IR=1,MODE
DO 26 IC=1,NCONTR
A(IR,IC+MODE3)=W7(IR,IC)
26 CONTINUE
RETURN
END

```

```

SUBROUTINE ARITH (SA,A,SB,B,C,NR,NC)
C*****
C
C   PROGRAM ARITH      (ARTIHMETIC)
C
C*****
C
C   THIS PROGRAM WILL MULTIPLE A MATRIX BY A CONSTANT AND ADD IT TO SECOND
C   MATRIX OF THE SAME SIZE AFTER THE SECOND MATRIX HAS BEEN MULTIPLIED BY
C   A SECOND CONSTANT.
C
C   SA      = CONSTANT THAT WILL MULTIPLY THE "A" MATRIX
C   A       = NR BY NC MATRIX
C   SB      = CONSTANT THAT WILL MULTIPLY THE "B" MATRIX
C   B       = NR BY NC MATRIX
C   C       = NR BY NC MATRIX (SOLUTION OF (SA*A)+(SB*B))
C   NR      = NUMBER OF ROWS
C   NC      = NUMBER OF COLUMNS
C
C*****
C   DIMENSION A(NR,NC), B(NR,NC), C(NR,NC)
C   DO 500 IR=1,NR
C   DO 501 IC=1,NC
C   C(IR,IC)=SA*A(IR,IC) + SB*B(IR,IC)
501 CONTINUE
500 CONTINUE
RETURN
END
SUBROUTINE QBARC (MACH,ALT,U,QBAR,INFLG)
C*****
C
C   PROGRAM QBARC
C
C*****
C
C   THIS PROGRAM TAKES THE MACH NUMBER AND ALTITUDE AND ESTIMATES THE

```


C AIRSPEED IN FT/SEC AND THE DYNAMIC PRESSURE.

C

C*****

REAL MACH

DIMENSION ALTT(10), A(10), RHO(10)

DIMENSION BKMACH(10), CLCORR(10)

DATA ALTT/0.0,5000.,10000.,15000.,20000.,25000.,30000.,
.35000.,40000.,50000./

DATA A/1118.45,1097.09,1077.40,1057.35,1036.92,1016.10,

.994.85,973.14,968.08,968.08/

DATA RHO/.0023769,.0020482,.0017556,.0014962,.0012673,.0010663,

.00089069,.00073281,.00058728,.00036392/

DATA BKMACH/.70,.725,.75,.775,.80,.825,.85,.875,.90,.925/

DATA CLCORR/1.025,1.026,1.027,1.03,1.05,1.07,1.08,1.1,1.125,1.155/

IF (ALT.GT.0.0) GO TO 102

AI=A(1)

RHOI=RHO(1)

GO TO 103

102 CONTINUE

DO 200 I=1,10

ISAV=I

IF (ALT.LE.ALTT(I)) GO TO 100

200 CONTINUE

PRINT 950

950 FORMAT (10X,*ALT IS OUTSIDE TABLES. WILL USE RHO=0.0, VT=968.07*)

AI=968.07

RHOI=0.0

GO TO 103

100 CONTINUE

DZ=(ALT-ALTT(ISAV-1))/(ALTT(ISAV)-ALTT(ISAV-1))

RHOI=RHO(ISAV-1)+DZ*(RHO(ISAV)-RHO(ISAV-1))

AI=A(ISAV-1)+DZ*(A(ISAV)-A(ISAV-1))

103 CONTINUE

U=MACH*AI

QBAR=0.5*RHOI*U*U

C LIFT-CURVE SLOPE CORRECTION FACTOR

67

C

C

C

5

5
6

3

2

22

22

۲۲

2.

429.

430.

431.

437

465.

433.

424

435

436

437

1997

| | | |
|---|--|------|
| C | STABILIZED ELEMENTARY SIMILARITY TRANSFORMATIONS. | 438. |
| C | | 439. |
| C | ON INPUT: | 440. |
| C | | 441. |
| C | NM MUST BE SET TO THE ROW DIMENSION OF TWO-DIMENSIONAL | 442. |
| C | ARRAY PARAMETERS AS DECLARED IN THE CALLING PROGRAM | 443. |
| C | DIMENSION STATEMENT; | 444. |
| C | | 445. |
| C | N IS THE ORDER OF THE MATRIX; | 446. |
| C | | 447. |
| C | LOW AND IGH ARE INTEGERS DETERMINED BY THE BALANCING | 448. |
| C | SUBROUTINE BALANC. IF BALANC HAS NOT BEEN USED, | 449. |
| C | SET LOW=1, IGH=N; | 450. |
| C | | 451. |
| C | A CONTAINS THE INPUT MATRIX. | 452. |
| C | | 453. |
| C | ON OUTPUT: | 454. |
| C | | 455. |
| C | A CONTAINS THE HESSENBERG MATRIX. THE MULTIPLIERS | 456. |
| C | WHICH WERE USED IN THE REDUCTION ARE STORED IN THE | 457. |
| C | REMAINING TRIANGLE UNDER THE HESSENBERG MATRIX; | 458. |
| C | | 459. |
| C | INT CONTAINS INFORMATION ON THE ROWS AND COLUMNS | 460. |
| C | INTERCHANGED IN THE REDUCTION. | 461. |
| C | ONLY ELEMENTS LOW THROUGH IGH ARE USED; | 462. |
| C | | 463. |
| C | QUESTIONS AND COMMENTS SHOULD BE DIRECTED TO B. S. GAREOW; | 464. |
| C | | 466. |
| C | ----- | 467. |
| C | | 468. |
| C | LA = IGH - 1 | 469. |
| C | KP1 = LOW + 1 | 470. |
| C | IF (LA .LT. KP1) GO TO 200 | 471. |
| C | | 472. |
| C | DO 180 M = KP1, LA | 473. |
| C | MM1 = M - 1 | 474. |

| | | |
|-----|--|------|
| | X = 0.0E0 | 475. |
| | I = M | 476. |
| C | | 477. |
| | DO 100 J = M, IGH | 478. |
| | IF (ABS(A(J,MM1)) .LE. ABS(X)) GO TO 100 | |
| | X = A(J,MM1) | 480. |
| | I = J | 481. |
| 100 | CONTINUE | 482. |
| C | | 483. |
| | INT(M) = I | 484. |
| | IF (I .EQ. M) GO TO 130 | 485. |
| C | | |
| C | INTERCHANGE ROWS AND COLUMNS OF A | |
| | DO 110 J = MM1, N | 487. |
| | Y = A(I,J) | 488. |
| | A(I,J) = A(M,J) | 489. |
| | A(M,J) = Y | 490. |
| 110 | CONTINUE | 491. |
| C | | 492. |
| | DO 120 J = 1, IGH | 493. |
| | Y = A(J,I) | 494. |
| | A(J,I) = A(J,M) | 495. |
| | A(J,M) = Y | 496. |
| 120 | CONTINUE | 497. |
| C | | |
| C | END INTERCHANGE | |
| 130 | IF (X .EQ. 0.0E0) GO TO 180 | 499. |
| | MP1 = M + 1 | 500. |
| C | | 501. |
| | DO 160 I = MP1, IGH | 502. |
| | Y = A(I,MM1) | 503. |
| | IF (Y .EQ. 0.0E0) GO TO 160 | 504. |
| | Y = Y / X | 505. |
| | A(I,MM1) = Y | 506. |
| C | | 507. |
| | DO 140 J = M, N | 508. |

| | | |
|-----|---|------|
| 140 | A(I,J) = A(I,J) - Y * A(M,J) | 509. |
| C | | 510. |
| | DO 150 J = 1, IGH | 511. |
| 150 | A(J,M) = A(J,M) + Y * A(J,I) | 512. |
| C | | 513. |
| 160 | CONTINUE | 514. |
| C | | 515. |
| 180 | CONTINUE | 516. |
| C | | 517. |
| 200 | RETURN | 518. |
| C | | |
| | END | 520. |
| C | SUBROUTINE ELTRAN(NM,N,LOW,IGH,A,INT,Z) | 527. |
| | | 528. |
| | INTEGER I,J,N,KL,MM,MP,NM,IGH,LOW,MP1 | 529. |
| | REAL A(NM,IGH),Z(NM,N) | |
| | INTEGER INT(IGH) | 531. |
| C | | 532. |
| C | THIS SUBROUTINE IS A TRANSLATION OF THE ALGOL PROCEDURE ELMTRANS, | 533. |
| C | NUM. MATH. 16, 181-204(1970) BY PETERS AND WILKINSON. | 534. |
| C | HANDBOOK FOR AUTO. COMP., VOL.II-LINEAR ALGEBRA, 372-395(1971). | 535. |
| C | | 536. |
| C | THIS SUBROUTINE ACCUMULATES THE STABILIZED ELEMENTARY | 537. |
| C | SIMILARITY TRANSFORMATIONS USED IN THE REDUCTION OF A | 538. |
| C | REAL GENERAL MATRIX TO UPPER HESSENBERG FORM BY ELMHES. | 539. |
| C | | 540. |
| C | ON INPUT: | 541. |
| C | | 542. |
| C | NM MUST BE SET TO THE ROW DIMENSION OF TWO-DIMENSIONAL | 543. |
| C | ARRAY PARAMETERS AS DECLARED IN THE CALLING PROGRAM | 544. |
| C | DIMENSION STATEMENT; | 545. |
| C | | 546. |
| C | N IS THE ORDER OF THE MATRIX; | 547. |
| C | | 548. |
| C | LOW AND IGH ARE INTEGERS DETERMINED BY THE BALANCING | 549. |
| C | SUBROUTINE BALANC. IF BALANC HAS NOT BEEN USED, | 550. |

| | | |
|---|--|------|
| C | SET LOW=1, IGH=N; | 551. |
| C | | 552. |
| C | A CONTAINS THE MULTIPLIERS WHICH WERE USED IN THE | 553. |
| C | REDUCTION BY ELMHES IN ITS LOWER TRIANGLE | 554. |
| C | BELOW THE SUBDIAGONAL; | 555. |
| C | | 556. |
| C | INT CONTAINS INFORMATION ON THE ROWS AND COLUMNS | 557. |
| C | INTERCHANGED IN THE REDUCTION BY ELMHES. | 558. |
| C | ONLY ELEMENTS LOW THROUGH IGH ARE USED. | 559. |
| C | | 560. |
| C | ON OUTPUT: | 561. |
| C | | 562. |
| C | Z CONTAINS THE TRANSFORMATION MATRIX PRODUCED IN THE | 563. |
| C | REDUCTION BY ELMHES. | 564. |
| C | | 565. |
| C | QUESTIONS AND COMMENTS SHOULD BE DIRECTED TO B. S. GARBOW, | 566. |
| C | APPLIED MATHEMATICS DIVISION, ARGONNE NATIONAL LABORATORY | 567. |
| C | | 568. |
| C | ----- | 569. |
| C | | 570. |
| C | INITIALIZE Z TO IDENTITY MATRIX | |
| C | DO 80 I = 1, N | 572. |
| C | | 573. |
| C | DO 60 J = 1, N | 574. |
| C | 60 Z(I,J) = 0.0E0 | 575. |
| C | | 576. |
| C | Z(I,I) = 1.0E0 | 577. |
| C | 80 CONTINUE | 578. |
| C | | 579. |
| C | KL = IGH - LOW - 1 | 580. |
| C | IF (KL .LT. 1) GO TO 200 | 581. |
| C | FOR MP=IGH-1 STEP -1 UNTIL LOW+1 DO -- | |
| C | | |
| C | DO 140 MM = 1, KL | 583. |
| C | MP = IGH - MM | 584. |

| | | |
|-----|---|------|
| C | MP1 = MP + 1 | 585. |
| C | DO 100 I = MP1, IGH | 586. |
| 100 | Z(I,MP) = A(I,MP-1) | 587. |
| C | I = INT(MP) | 588. |
| C | IF (I .EQ. MP) GO TO 140 | 589. |
| C | DO 130 J = MP, IGH | 590. |
| | Z(MP,J) = Z(I,J) | 591. |
| | Z(I,J) = 0.0E0 | 592. |
| 130 | CONTINUE | 593. |
| C | Z(I,MP) = 1.0E0 | 594. |
| 140 | CONTINUE | 595. |
| C | 200 RETURN | 596. |
| C | END | 597. |
| C | SUBROUTINE HQR2(NM,N,LOW,IGH,H,WR,WI,Z,IERR,INUM) | 598. |
| | INTEGER I,J,K,L,M,N,EN,II,JJ,LL,MM,NA,NM,NN, | 599. |
| X | IGH,ITS,LOW,MP2,ENM2,IERR | 600. |
| | REAL H(NM,N),WR(N),WI(N),Z(NM,N) | 601. |
| | REAL P,Q,R,S,T,W,X,Y,RA,SA,VI,VR,ZZ,NORM,MACHEP | 603. |
| | INTEGER MINO | 7. |
| | LOGICAL NOTLAS | 8. |
| | COMPLEX Z3 | 9. |
| | COMPLEX CMPLX | 13. |
| | REAL T3(2) | 14. |
| | EQUIVALENCE (Z3,T3(1)) | 18. |
| C | THIS SUBROUTINE IS A TRANSLATION OF THE ALGOL PROCEDURE HQR2, | 19. |
| C | NUM. MATH. 16, 181-204(1970) BY PETERS AND WILKINSON. | 20. |
| C | HANDBOOK FOR AUTO. COMP., VOL.II-LINEAR ALGEBRA, 372-395(1971). | 21. |
| C | | 22. |
| C | | 23. |

| | | |
|---|--|-----|
| C | THIS SUBROUTINE FINDS THE EIGENVALUES AND EIGENVECTORS | 24. |
| C | OF A REAL UPPER HESSENBERG MATRIX BY THE QR METHOD. THE | 25. |
| C | EIGENVECTORS OF A REAL GENERAL MATRIX CAN ALSO BE FOUND | 26. |
| C | IF ELMHES AND ELTRAN OR ORTHES AND ORTRAN HAVE | 27. |
| C | BEEN USED TO REDUCE THIS GENERAL MATRIX TO HESSENBERG FORM | 28. |
| C | AND TO ACCUMULATE THE SIMILARITY TRANSFORMATIONS. | 29. |
| C | | 30. |
| C | ON INPUT: | 31. |
| C | | 32. |
| C | NM MUST BE SET TO THE ROW DIMENSION OF TWO-DIMENSIONAL | 33. |
| C | ARRAY PARAMETERS AS DECLARED IN THE CALLING PROGRAM | 34. |
| C | DIMENSION STATEMENT; | 35. |
| C | | 36. |
| C | N IS THE ORDER OF THE MATRIX; | 37. |
| C | | 38. |
| C | LOW AND IGH ARE INTEGERS DETERMINED BY THE BALANCING | 39. |
| C | SUBROUTINE BALANC. IF BALANC HAS NOT BEEN USED, | 40. |
| C | SET LOW=1, IGH=N; | 41. |
| C | | 42. |
| C | H CONTAINS THE UPPER HESSENBERG MATRIX; | 43. |
| C | | 44. |
| C | Z CONTAINS THE TRANSFORMATION MATRIX PRODUCED BY ELTRAN | 45. |
| C | AFTER THE REDUCTION BY ELMHES, OR BY ORTRAN AFTER THE | 46. |
| C | REDUCTION BY ORTHES, IF PERFORMED. IF THE EIGENVECTORS | 47. |
| C | OF THE HESSENBERG MATRIX ARE DESIRED, Z MUST CONTAIN THE | 48. |
| C | IDENTITY MATRIX. | 49. |
| C | | 50. |
| C | ON OUTPUT: | 51. |
| C | | 52. |
| C | H HAS BEEN DESTROYED; | 53. |
| C | | 54. |
| C | WR AND WI CONTAIN THE REAL AND IMAGINARY PARTS, | 55. |
| C | RESPECTIVELY, OF THE EIGENVALUES. THE EIGENVALUES | 56. |
| C | ARE UNORDERED EXCEPT THAT COMPLEX CONJUGATE PAIRS | 57. |
| C | OF VALUES APPEAR CONSECUTIVELY WITH THE EIGENVALUE | 58. |
| C | HAVING THE POSITIVE IMAGINARY PART FIRST. IF AN | 59. |

| | | |
|---|--|-----|
| C | ERROR EXIT IS MADE, THE EIGENVALUES SHOULD BE CORRECT | 60. |
| C | FOR INDICES IERR+1.....N; | 61. |
| C | | 62. |
| C | Z CONTAINS THE REAL AND IMAGINARY PARTS OF THE EIGENVECTORS. | 63. |
| C | IF THE I-TH EIGENVALUE IS REAL, THE I-TH COLUMN OF Z | 64. |
| C | CONTAINS ITS EIGENVECTOR. IF THE I-TH EIGENVALUE IS COMPLEX | 65. |
| C | WITH POSITIVE IMAGINARY PART, THE I-TH AND (I+1)-TH | 66. |
| C | COLUMNS OF Z CONTAIN THE REAL AND IMAGINARY PARTS OF ITS | 67. |
| C | EIGENVECTOR. THE EIGENVECTORS ARE UNNORMALIZED. IF AN | 68. |
| C | ERROR EXIT IS MADE, NONE OF THE EIGENVECTORS HAS BEEN FOUND; | 69. |
| C | | 70. |
| C | IERR IS SET TO | 71. |
| C | ZERO FOR NORMAL RETURN, | 72. |
| C | J IF THE J-TH EIGENVALUE HAS NOT BEEN | 73. |
| C | DETERMINED AFTER 30 ITERATIONS. | 74. |
| C | | 75. |
| C | ARITHMETIC IS REAL EXCEPT FOR THE REPLACEMENT OF THE ALGOL | 76. |
| C | PROCEDURE CDIV BY COMPLEX DIVISION. | 77. |
| C | | 78. |
| C | QUESTIONS AND COMMENTS SHOULD BE DIRECTED TO B. S. GARROW, | 79. |
| C | APPLIED MATHEMATICS DIVISION, ARGONNE NATIONAL LABORATORY | 80. |
| C | | 81. |
| C | ----- | 82. |
| C | | |
| C | MACHEP IS A MACHINE DEPENDENT PARAMETER SPECIFYING | 84. |
| C | THE RELATIVE PRECISION OF FLOATING POINT ARITHMETIC. | 85. |
| C | MACHEP = 16.0E0*(-13) FOR LONG FORM ARITHMETIC | 86. |
| C | ON S360 | |
| C | DATA MACHEP/1.E-9/ | |
| C | | 89. |
| C | DO 5 K=1,IGH | |
| C | WR(K)=0. | |
| C | WI(K)=0. | |
| C | 5 CONTINUE | |
| C | IERR = 0 | 90. |
| C | | |

| | | |
|---|--|------|
| C | STORE ROOTS ISOLATED BY BALANC | |
| | DO 50 I = 1, N | 92. |
| | IF (I .GE. LOW .AND. I .LE. IGH) GO TO 50 | 93. |
| | WR(I) = H(I,I) | 94. |
| | WI(I) = 0.0E0 | 95. |
| | 50 CONTINUE | 96. |
| C | | 97. |
| | EN = IGH | 98. |
| | T = 0.0E0 | 99. |
| C | | |
| C | SEARCH FOR NEXT EIGENVALUES | |
| | 60 IF (EN .LT. LOW) GO TO 340 | 101. |
| | ITS = 0 | 102. |
| | NA = EN - 1 | 103. |
| | ENM2 = NA - 1 | 104. |
| C | | |
| C | LOOK FOR SINGLE SMALL SUB-DIAGONAL ELEMENT | |
| C | FOR L=EN STEP -1 UNTIL LOW DO -- | |
| | 70 DO 80 LL = LOW, EN | 107. |
| | L = EN + LOW - LL | 108. |
| | IF (L .EQ. LOW) GO TO 100 | 109. |
| | IF (ABS(H(L,L-1)) .LE. MACHEP * (ABS(H(L-1,L-1)) | |
| | X + ABS(H(L,L)))) GO TO 100 | |
| | 80 CONTINUE | 112. |
| C | | |
| C | FORM SHIFT | |
| | 100 X = H(EN,EN) | 114. |
| | IF (L .EQ. EN) GO TO 270 | 115. |
| | Y = H(NA,NA) | 116. |
| | W = H(EN,NA) + H(NA,EN) | 117. |
| | IF (L .EQ. NA) GO TO 280 | 118. |
| | IF (ITS .EQ. 30) GO TO 1000 | 119. |
| | IF (ITS .NE. 10 .AND. ITS .NE. 20) GO TO 130 | 120. |
| C | | |
| C | FORM EXCEPTIONAL SHIFT | |
| | T = T + X | 122. |

| | | |
|---|--|------|
| C | | 123. |
| | DO 120 I = LOW, EN | 124. |
| | 120 H(I,I) = H(I,I) - X | 125. |
| C | | 126. |
| | S = ABS(H(EN,NA)) + ABS(H(NA,ENM2)) | |
| | X = 0.75E0 * S | 128. |
| | Y = X | 129. |
| | W = -0.4375E0 * S * S | 130. |
| | 130 ITS = ITS + 1 | 131. |
| C | | |
| C | LOOK FOR TWO CONSECUTIVE SMALL | |
| C | SUB-DIAGONAL ELEMENTS. | 133. |
| C | FOR M=EN-2 STEP -1 UNTIL L DO -- | |
| | DO 140 MM = L, ENM2 | 135. |
| | M = ENM2 + L - MM | 136. |
| | ZZ = H(M,M) | 137. |
| | R = X - ZZ | 138. |
| | S = Y - ZZ | 139. |
| | P = (R * S - W) / H(M+1,M) + H(M,M+1) | 140. |
| | Q = H(M+1,M+1) - ZZ - R - S | 141. |
| | R = H(M+2,M+1) | 142. |
| | S=ABS(P)+ABS(Q)+ABS(R) | |
| | P = P / S | 144. |
| | Q = Q / S | 145. |
| | R = R / S | 146. |
| | IF (M .EQ. L) GO TO 150 | 147. |
| | IF (ABS(H(M,M-1)) * (ABS(Q) + ABS(R)) .LE. MACHEP * ABS(P) | 148. |
| X | * (ABS(H(M-1,M-1)) + ABS(ZZ) + ABS(H(M+1,M+1))) GO TO 150 | 149. |
| | 140 CONTINUE | 150. |
| | 150 MP2 = M + 2 | 152. |
| | DO 160 I = MP2, EN | 154. |
| | H(I,I-2) = 0.0E0 | 155. |
| | IF (I .EQ. MP2) GO TO 160 | 156. |
| | H(I,I-3) = 0.0E0 | 157. |
| | 160 CONTINUE | 158. |
| C | DOUBLE OR STEP INVOLVING ROWS L TO EN AND, | |

C

COLUMNS M TO EN

DO 260 K = M, NA

NOTLAS = K .NE. NA

IF (K .EQ. M) GO TO 170

P = H(K,K-1)

Q = H(K+1,K-1)

R = 0.0E0

IF (NOTLAS) R = H(K+2,K-1)

X = ABS(P) + ABS(Q) + ABS(R)

IF (X .EQ. 0.0E0) GO TO 260

P = P / X

Q = Q / X

R = R / X

170 S = SIGN(SORT(P*P+Q*Q+R*R), P)

IF (K .EQ. M) GO TO 180

H(K,K-1) = -S * X

GO TO 190

180 IF (L .NE. M) H(K,K-1) = -H(K,K-1)

190 P = P + S

X = P / S

Y = Q / S

ZZ = R / S

Q = Q / P

R = R / P

C

C

ROW MODIFICATION

DO 210 J = K, N

P = H(K,J) + Q * H(K+1,J)

IF (.NOT. NOTLAS) GO TO 200

P = P + R * H(K+2,J)

H(K+2,J) = H(K+2,J) - P * Z

200 H(K+1,J) = H(K+1,J) - P * Y

H(K,J) = H(K,J) - P * X

210 CONTINUE

C

J = MIN0(EN,K+3)

161.

162.

163.

164.

165.

166.

167.

169.

170.

171.

172.

174.

175.

176.

177.

178.

179.

180.

181.

182.

183.

185.

186.

187.

188.

189.

190.

191.

192.

193.

194.

| | | |
|-----|-------------------------------|------|
| C | | |
| C | COLUMN MODIFICATION | |
| | DO 230 I = 1, J | 196. |
| | P = X * H(I,K) + Y * H(I,K+1) | 197. |
| | IF (.NOT. NOTLAS) GO TO 220 | 198. |
| | P = P + ZZ * H(I,K+2) | 199. |
| | H(I,K+2) = H(I,K+2) - P * R | 200. |
| 270 | H(I,K+1) = H(I,K+1) - P * Q | 201. |
| | H(I,K) = H(I,K) - P | 202. |
| 230 | CONTINUE | 203. |
| C | | |
| C | ACCUMULATE TRANSFORMATIONS | |
| | DO 250 I = LDH, IGH | 205. |
| | P = X * Z(I,K) + Y * Z(I,K+1) | 206. |
| | IF (.NOT. NOTLAS) GO TO 240 | 207. |
| | P = P + ZZ * Z(I,K+2) | 208. |
| | Z(I,K+2) = Z(I,K+2) - P * R | 209. |
| 240 | Z(I,K+1) = Z(I,K+1) - P * Q | 210. |
| | Z(I,K) = Z(I,K) - P | 211. |
| 250 | CONTINUE | 212. |
| C | | 213. |
| | 260 CONTINUE | 214. |
| C | | 215. |
| | GO TO 70 | 216. |
| C | | |
| C | ONE ROOT FOUND | |
| 270 | H(EN,EN) = X + T | 218. |
| | HR(EN) = H(EN,EN) | 219. |
| | HI(EN) = 0.0E0 | 220. |
| | EN = NA | 221. |
| | GO TO 60 | 222. |
| C | | |
| C | TWO ROOTS FOUND | |
| 280 | P = (Y - X) / 2.0E0 | 224. |
| | Q = P * P + W | 225. |
| | ZZ = SORT(ABS(Q)) | |

227.
228.
229.
230.
233.
234.
235.
236.
237.
238.
240.
241.
243.
244.
245.
246.
247.
249.
250.
251.
252.
253.
255.
256.
257.
258.

H(EN,EN) = X + T
H(NA,NA) = Y + T
IF (Q.LT. 0.0EO) GO TO 320
REAL PAIR
ZZ = P + SIGN(ZZ,P)
WR(NA) = X + ZZ
WR(EN) = WR(NA)
IF (ZZ.NE. 0.0EO) WR(EN) = X / ZZ
W(NA) = 0.0EO
W(EN) = 0.0EO
X = H(EN,NA)
R = SORT(X*X+ZZ*ZZ)
P = X / R
Q = ZZ / R
ROW MODIFICATION
DO 290 J = NA, N
ZZ = H(NA,J)
H(NA,J) = Q * ZZ + P * H(EN,J)
H(EN,J) = Q * H(EN,J) - P * ZZ
290 CONTINUE
COLUMN MODIFICATION
DO 300 I = 1, EN
ZZ = H(I,NA)
H(I,NA) = Q * ZZ + P * H(I,EN)
H(I,EN) = Q * H(I,EN) - P * ZZ
300 CONTINUE
ACCUMULATE TRANSFORMATIONS
DO 310 I = LOW, HIGH
ZZ = Z(I,NA)
Z(I,NA) = Q * ZZ + P * Z(I,EN)
Z(I,EN) = Q * Z(I,EN) - P * ZZ

C
C

C
C

C
C

C
C

| | |
|---|------|
| 310 CONTINUE | 259. |
| C | 260. |
| GO TO 330 | 261. |
| C | |
| COMPLEX PAIR | |
| 320 WR(NA) = X' + P | 263. |
| WR(EN) = X + P | 264. |
| WI(NA) = ZZ | 265. |
| WI(EN) = -ZZ | 266. |
| 330 EN = ENM2 | 267. |
| GO TO 60 | 268. |
| C | |
| ALL ROOTS FOUND. BACKSUBSTITUTE TO FIND | |
| C | |
| VECTORS OF UPPER TRIANGULAR FORM | |
| 340 IF (INUM.EQ.1) RETURN | |
| NORM=0.0E0 | |
| K = 1 | 272. |
| C | 273. |
| DO 360 I = 1, N | 274. |
| C | 275. |
| DO 350 J = K, N | 276. |
| 350 NORM=NORM+ABS(H(I,J)) | |
| C | 278. |
| K = I | 279. |
| 360 CONTINUE | 280. |
| C | 281. |
| IF (NORM .EQ. 0.0E0) GO TO 1001 | 282. |
| C | |
| FOR EN=N STEP -1 UNTIL 1 DO -- | |
| DO 800 NN = 1, N | 284. |
| EN = N + 1 - NN | 285. |
| P = WR(EN) | 286. |
| Q = WI(EN) | 287. |
| NA = EN - 1 | 288. |
| IF (Q) 710, 800, 800 | 289. |
| C | |

| | | |
|-----|---|------|
| 600 | M = EN | 291. |
| | H(EN,EN) = 1.0E0 | 292. |
| | IF (NA .EQ. 0) GO TO 800 | 293. |
| C | | |
| C | FOR I=EN-1 STEP -1 UNTIL 1 DO -- | |
| | DO 700 II = 1, NA | 295. |
| | I = EN - II | 296. |
| | W = H(I,I) - P | 297. |
| | R = H(I,EN) | 298. |
| | IF (M .GT. NA) GO TO 620 | 299. |
| C | | 300. |
| | DO 610 J = M, NA | 301. |
| 610 | R = R + H(I,J) * H(J,EN) | 302. |
| C | | 303. |
| 620 | IF (W(I) .GE. 0.0E0) GO TO 630 | 304. |
| | ZZ = W | 305. |
| | S = R | 306. |
| | GO TO 700 | 307. |
| 630 | M = I | 308. |
| | IF (W(I) .NE. 0.0E0) GO TO 640 | 309. |
| | T = W | 310. |
| | IF (W .EG. 0.0E0) T = MACHEP * NORM | 311. |
| | H(I,EN) = -R / T | 312. |
| | GO TO 700 | 313. |
| C | | |
| C | SOLVE REAL EQUATIONS | |
| 640 | X = H(I,I+1) | 315. |
| | Y = H(I+1,I) | 316. |
| | Q = (W(I) - P) * (W(I) - P) + W(I) * W(I) | 317. |
| | T = (X * S - ZZ * R) / Q | 318. |
| | H(I,EN) = T | 319. |
| | IF (ABS(X) .LE. ABS(ZZ)) GO TO 650 | |
| | H(I+1,EN) = (-R - W * T) / X | 321. |
| | GO TO 700 | 322. |
| 650 | H(I+1,EN) = (-S - Y * T) / ZZ | 323. |
| 700 | CONTINUE | 324. |

| | | | |
|-----|---|--|------|
| C | | | |
| C | END REAL VECTOR | | |
| | GO TO 800 | | 326. |
| C | | | |
| C | COMPLEX VECTOR | | |
| 710 | M = NA | | 328. |
| C | | | |
| C | LAST VECTOR COMPONENT CHOSEN IMAGINARY SO THAT | | |
| C | EIGENVECTOR MATRIX IS TRIANGULAR | | |
| | IF (ABS(H(EN,NA)) .LE. ABS(H(NA,EN))) GO TO 720 | | |
| | H(NA,NA) = Q / H(EN,NA) | | 332. |
| | H(NA,EN) = -(H(EN,EN) - P) / H(EN,NA) | | 333. |
| | GO TO 730 | | 334. |
| 720 | Z3 = CMPLX(0.0E0, -H(NA,EN)) / CMPLX(H(NA,NA) - P, Q) | | |
| | H(NA,NA) = T3(1) | | 336. |
| | H(NA,EN) = T3(2) | | 337. |
| 730 | H(EN,NA) = 0.0E0 | | 338. |
| | H(EN,EN) = 1.0E0 | | 339. |
| | ENM2 = NA - 1 | | 340. |
| | IF (ENM2 .EQ. 0) GO TO 800 | | 341. |
| C | | | 342. |
| | DO 790 II = 1, ENM2 | | 343. |
| | I = NA - II | | 344. |
| | W = H(I, I) - P | | 345. |
| | RA = 0.0E0 | | 346. |
| | SA = H(I, EN) | | 347. |
| C | | | 348. |
| | DO 760 J = M, NA | | 349. |
| | RA = RA + H(I, J) * H(J, NA) | | 350. |
| | SA = SA + H(I, J) * H(J, EN) | | 351. |
| 760 | CONTINUE | | 352. |
| C | | | 353. |
| | IF (W(1) .GE. 0.0E0) GO TO 770 | | 354. |
| | ZZ = W | | 355. |
| | R = RA | | 356. |
| | S = SA | | 357. |

| | | |
|-----|---|------|
| | GO TO 790 | 358. |
| 770 | M = 1 | 359. |
| | IF (W1(I) .NE. 0.0E0) GO TO 780 | 360. |
| | Z3 = CMPLX(-RA,-SA) / CMPLX(W,Q) | |
| | H(I,NA) = T3(1) | 362. |
| | H(I,EN) = T3(2) | 363. |
| | GO TO 790 | 364. |
| C | | |
| C | SOLVE COMPLEX EQUATIONS | |
| 780 | X = H(I,I+1) | 366. |
| | Y = H(I+1,I) | 367. |
| | VR = (WR(I) - P) * (WR(I) - P) + WI(I) * WI(I) - Q * Q | 368. |
| | VI = (WR(I) - P) * 2.0E0 * Q | 369. |
| | IF (VR .EQ. 0.0E0 .AND. VI .EQ. 0.0E0) VR = MACHEP * NORM | 370. |
| X | * (ABS(W) + ABS(Q) + ABS(X) + ABS(Y) + ABS(ZZ)) | |
| | Z3 = CMPLX(X*R-ZZ*RA+Q*SA,X*S-ZZ*SA-Q*RA) / CMPLX(VR,VI) | 372. |
| | H(I,NA) = T3(1) | 373. |
| | H(I,EN) = T3(2) | 374. |
| | IF (ABS(X) .LE. ABS(ZZ) + ABS(Q)) GO TO 785 | |
| | H(I+1,NA) = (-RA - W * H(I,NA) + Q * H(I,EN)) / X | 376. |
| | H(I+1,EN) = (-SA - W * H(I,EN) - Q * H(I,NA)) / X | 377. |
| | GO TO 790 | 378. |
| 785 | Z3 = CMPLX(-R-Y*H(I,NA),-S-Y*H(I,EN)) / CMPLX(ZZ,Q) | |
| | H(I+1,NA) = T3(1) | 380. |
| | H(I+1,EN) = T3(2) | 381. |
| 790 | CONTINUE | 382. |
| C | | |
| C | END COMPLEX VECTOR | |
| 800 | CONTINUE | 384. |
| C | | |
| C | END BACK SUBSTITUTION. | |
| C | VECTORS OF ISOLATED ROOTS | |
| | DO 840 I = 1, N | 387. |
| | IF (I .GE. LOW .AND. I .LE. IGH) GO TO 840 | 388. |
| C | | 389. |
| | DO 820 J = 1, N | 390. |

| | | |
|------|--|------|
| 820 | Z(I,J) = H(I,J) | 391. |
| C | | 392. |
| 840 | CONTINUE | 393. |
| C | | |
| C | MULTIPLY BY TRANSFORMATION MATRIX TO GIVE | 395. |
| C | VECTORS OF ORIGINAL FULL MATRIX. | 396. |
| C | FOR J=N STEP -1 UNTIL LOW DO -- :::::::::: | 397. |
| C | DO 880 JJ = LOW, N | 398. |
| | J = N + LOW - JJ | 399. |
| | M = MINO(J,IGH) | 400. |
| C | | 401. |
| | DO 880 I = LOW, IGH | 402. |
| | ZZ = 0.0E0 | 403. |
| C | | 404. |
| | DO 860 K = LOW, M | 405. |
| 860 | ZZ = ZZ + Z(I,K) * H(K,J) | 406. |
| C | | 407. |
| | Z(I,J) = ZZ | 408. |
| 880 | CONTINUE | 409. |
| C | | 410. |
| | GO TO 1001 | |
| C | | |
| C | SET ERROR -- NO CONVERGENCE TO AN | |
| C | EIGENVALUE AFTER 30 ITERATIONS | 413. |
| 1000 | IERR = EN | 414. |
| 1001 | RETURN | |
| C | | |
| C | LAST CARD OF HQR2 | 416. |
| | END | |
| | END OF FILE | |

APPENDIX D

SAMPLE INPUT FILE FOR "SAFSS".

| | | | |
|---------------------|---------------------|---------------------|---------------------|
| 0. | 0. | .2250000000000E+07 | -.2976191000000E+08 |
| -.1632200000000E+06 | -.2156364000000E+10 | -.2880000000000E+07 | -.3364000000000E+04 |
| -.1000000000000E+03 | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | .1000000000000E+01 | 0. |
| 0. | 0. | 0. | 0. |
| -.1204563600000E+06 | -.1591396632000E+10 | .1660500000000E+07 | -.2196428958000E+08 |
| 0. | -.1254400000000E+05 | -.2125440000000E+07 | .1237626000000E+04 |
| 0. | 0. | -.1000000000000E+03 | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| .1000000000000E+01 | 0. | 0. | 0. |
| 0. | 0. | .1660500000000E+07 | -.2196428958000E+08 |
| -.1204563600000E+06 | -.1591396632000E+10 | -.2125440000000E+07 | .1237626000000E+04 |
| 0. | .1568000000000E+05 | 0. | -.8720209000000E+05 |
| -.7678000000000E+02 | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | .1000000000000E+01 | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | -.1934240400000E+06 | -.5894000000000E+03 | .8720209000000E+05 |
| .1000000000000E+01 | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | 0. | 0. | 0. |
| 0. | .1934000000000E+06 | 0. | 0. |

ORIGINAL PAGE IS
OF POOR QUALITY

.825

T

.92039179144393E-01-.11654315425123E-01-.12552934386826E+00 .12991616531590E+00
-.16731513315278E+00-.54906550467919E-01 .11232242190525E+00-.33951599821190E-01
.25661250399087E+00 .23728743975749E+00 .10118167346036E-02
.58621245639060E+00-.25110777647203E+01 .12924344889389E+01-.12036663230693E+01
.83569732004162E+00 .16822540652744E+01-.17036101994468E+01 .14169123542322E+01
-.92846729342097E+00 .16730890244924E+00 .70324919680479E+00
-.20102552364770E+01 .13479801415545E+01-.28893520097497E+01-.75631838856816E+00
.59551572876444E-02-.10211708574411E+01 .11019380405796E+01-.24411171257506E+01
-.45899823654896E+01 .35874013177045E+00-.11552424058953E+01
.32648265353059E+01 .30501324024654E+00-.39416094664588E+00-.53470166785280E+00
.79438629650588E+00 .95398101539848E+00 .40709346637868E-01-.72162782782854E-01
.15688021899916E+01-.16164745279093E+00 .53470199487151E+00
-.24663332815949E+01-.60636874363625E+00 .55945127470874E+00 .19191692819152E+00
-.52778083708534E+00-.57664803542914E+00-.5223372994092E-01 .27506987432007E+00
-.16958864889228E+01 .15347589086946E+00-.29197626878675E+00
-.55199340125432E+00-.50236211061420E+00 .71023294701155E+00 .47708432986360E+00
-.47950990176764E+00 .55401111151139E+00-.15709235810732E+00 .75165332848883E-01
-.65173936262130E+00-.92891980944570E-01 .82061746183354E+00
-.98498704396806E+00-.67096859655962E-01 .23079295937717E+00 .81651303150363E+00
-.90595146986539E+00 .12797302193610E+00-.25009025732607E+00 .51424269756672E+00
-.99314303749173E+00 .26285576309988E+00 .24680836427240E+00
-.43482670248692E+00 .54066781255981E+00-.44241813951027E+00-.38435599792669E+00
.14228218653233E+00 .51193680855241E+00 .10016069831443E+01-.27097624361962E+01
-.31238103462393E+01-.38694783048555E+00-.26136145461874E+00
-.73850091031787E+00 .11505315155233E-01 .66918583743035E+00 .24156012804542E+00
-.34263468442782E+00 .76670511740588E+00 .88394703731092E+00-.17848176806006E+01
-.23875742043448E+01-.40149807721605E+00 .54819872835219E+00
.25887043032005E+00-.29191967602173E+00-.38190900917604E+00-.88921129390110E+00
.73458594624844E+00 .15144635475451E+00-.10467828617440E+01-.55934779315791E+00
-.69569905629664E+00 .37797152162693E+00-.60139778707298E+00
-.35434242490282E+00-.12336329472674E-01-.37383658755999E+00 .32397609793043E+00
-.54754457791682E+00-.17790402055607E+00 .63507741636499E+00-.10993986200609E+01
-.52008283947555E+00 .29293621564148E+00 .32228651585433E+00
-.28316254435903E+02-.36922253262744E+01-.36554036997203E+01 .20863227313002E+01

-.23410501323667E+01 .34748537215446E+01 .50723884273585E+01-.10943066566818E+01
 .15902336097438E+01-.48312822837527E+01-.16574736441863E+01
 -.87174673039796E+03 .98147694211804E+01 .19220848940156E+02-.48600103690884E+02
 .52555295375289E+02 .65457822999557E+01-.10691188275147E+02 .18073525856157E+01
 .47459335700241E+01-.10681864551282E+02 .58666755885648E+00
 .44105495890696E+02-.73482818970111E+01-.17079864340348E+02 .48485980288144E+02
 -.41808640326354E+02-.43472723397828E+01-.29025708591183E+02 .21615742960457E+01
 .53562940758184E-01-.59176413859617E+02 .14674504561756E+02
 -.27824757927811E+03 .18677888843947E+02 .31509598914606E+02-.11441377471712E+03
 .11188344608313E+03 .40186091283616E+01-.24260696859121E+02 .66174521656123E-01
 -.35600731261411E+01 .36301360315489E+02-.17112351187734E+02
 .74055513182824E+02-.13795641143187E+02-.25020512271379E+02 .99168837671441E+02
 -.96440927084780E+02 .79331550042085E+00 .29348305843109E+02-.57223026050397E+00
 .46467135474532E+01-.32873051418308E+02 .14543137733572E+02
 .66989540899283E+02-.56209442405572E+01-.62799871302191E+01 .13056769692640E+01
 -.21468288422260E+01-.10389941389754E+02-.13445327337460E+02 .21918986568037E+01
 -.10486885851200E+02 .27467613664136E+02-.81563492557343E+01
 .39322618284221E+03-.14753187903035E+02-.14044618255786E+02 .13588717047707E+02
 -.12875903754838E+02-.10993241586604E+02-.48960419563177E+02 .90877047842612E+01
 -.89326974537793E+01 .17880693041715E+02 .15960474637689E+01
 -.42032063698222E+02 .52919142777412E+01-.38323305457888E+01 .17269287355304E+01
 -.65987918611850E+00-.64518689683676E+00-.25177438572896E+00-.43105767851042E+01
 -.68084936285713E+01-.86699934266578E+01-.83478525248761E+01
 .11978457557420E+03-.59330739659482E+00-.89894267187564E+01 .42471838162885E+01
 -.52552762878968E+01-.10737170366134E+02-.14193657067264E+02-.39784104653509E+00
 -.16833334417793E+02 .36576551592823E+02-.14628835018360E+02
 -.40227748361018E+03 .85093469503675E+01 .63575844560278E+01 .70327528698101E+00
 .37662642256966E+01 .15616143623346E+02 .39024356332322E+02-.10222673905792E+02
 .21379649759334E+02-.99084558688146E+02 .11716314064118E+02
 .13043285359691E+03-.10300579229145E+02-.12941784763901E+02 .20334411014025E+02
 -.18739217323978E+02-.16505033760058E+02-.25069637169307E+02 .58163660858281E+00
 -.13153465477671E+02 .68077319107801E+01-.55739009226153E+01
 -.54844296202973E+02-.41478917581746E+01-.64523501424803E+01 .27063509598366E+02
 -.28085711242721E+02-.86497331844187E-01 .24113772677008E+02-.25637019788490E+01
 .22506703373698E+01-.34986618865990E+01 .23804693579243E+01
 -.30137938773770E+04-.11719386319587E+02 .22427381960061E+02 .17488317952889E+03

ORIGINAL PAGE IS
 OF POOR QUALITY

..19147263672297E+03 .19383002326155E+01 .11886169374785E+03 .15348703039825E+02
-.12949504932573E+03 .62635253288503E+03-.14220689552270E+03
.14421018867905E+03 .50770051431440E+01-.70609770551464E+01 .62111327287042E+02
-.84817446688314E+02-.18716296087002E+02 .11376028987670E+01 .20825246022869E+02
-.13046152726081E+03 .56312342897197E+03-.10484618271959E+03
-.13604205427455E+04-.28585916285834E+01 .80837596312301E+00-.42626869591150E+02
.61780569634494E+02 .17575922673093E+02 .18148660941254E+01-.13071672852439E+02
.74067086466879E+02-.29924925298366E+03 .50561039434504E+02
.51018275664745E+03 .10038158303539E+01-.42962842481220E+01 .63594787312663E+02
-.83326439249458E+02-.14755691865287E+02 .24232518206760E+02 .12668151825561E+02
-.83955944402628E+02 .36025673916625E+03-.67134500147037E+02
.27305530225092E+03-.33584056013845E+01-.22166280291548E+01 .17190279426658E+02
-.17264375578391E+02-.28539474067585E+01 .46401785661669E+01 .26784476690938E+01
-.21666940007385E+01-.31918821899603E+01-.66269949599385E+01
.15523866166556E+04-.90016805027577E+00-.26978881648732E+01 .57178179578883E+01
-.87968204414007E+01-.67053685766076E+01-.28980443003465E+02 .85881396921185E+01
-.86888760714756E+01 .23549282096882E+02 .10447108389754E+02
-.19224188495903E+03 .45529502187516E+01 .96978819476809E+00-.17534599022224E+02
.15775115193230E+02-.56195759037244E+01-.11666867470484E+02 .14238948188137E+01
-.21559137926217E+02 .78157595830413E+02-.26226096064333E+02
.51564536694907E+03 .32972016819310E+01 .28289118516515E+01-.31010115553371E+02
.32601157367370E+02-.91440350460321E+01-.34085155163512E+02 .29613739551999E+01
-.36777709730391E+01-.17332582422323E+02-.94202833464343E+01
-.17476351527789E+04-.37470562927037E+01-.95148205444707E+01 .71700041922159E+02
-.79909476869569E+02 .51153370281333E+01 .03010156684608E+02-.49933562327181E+01
-.35420782874133E+02 .17537479305902E+03-.43491568465755E+02
.59061879125863E+03-.14568247294605E+01-.36537630156258E+01 .30106182475570E+02
-.37684652034670E+02-.13944588975457E+02-.21580463150182E+02 .95540419184419E+01
-.48990052843586E+02 .16773426624502E+03-.50971753777993E+02
.20564254488671E+02 .44742053770105E+01 .14449930869777E+01-.29495074068992E+02
-.31161537477131E+02-.76133196683818E+00-.43053777830211E+01-.35369565752020E+01
.42442003207834E+01-.14122121370427E+01-.87888177026054E+00
.87198088824936E+03 .37739309233401E+01 .10804098033011E+01 .19839806747591E+02
.49395034794321E+02-.27526529099710E+01 .33165052037777E+01-.59850643457258E+00
.49520950010003E+01-.61647218474467E+01-.21952423424222E+01
-.73126414532083E+02-.10886902996630E+03-.20198454158909E+02 .96230154803595E+03

.10294284946105E+04 .57589954301509E+01 .11792957541278E+03 .29895413667553E+02
 -.42486394571673E+02 .66416269532389E+02 .82701211632067E+01
 .26486797294277E+03 .64676357201078E+02 .59518805458072E+01-.50688873793887E+03
 -.53656254944509E+03-.69240165874378E+01-.56376216487331E+02-.54606914992725E+01
 .15346551010292E+02-.39277375595955E+02-.21409583294777E+01
 -.59609576792676E+02-.46494897280932E+02-.46037835078468E+01 .43434287364156E+03
 .46639042268142E+03 .51232514465962E+01 .47575650340450E+02 .41771012867311E+01
 .11585404968995E+02 .31595147517030E+02 .13448848569767E+01
 -.67129607831250E+02-.70778308954557E+01 .10236099848492E+02 .16613197624908E+02
 .98967291561651E+01 .11137683560403E+01-.48404154352111E+01-.26334145720587E+02
 .21710684644463E+02 .68142480477079E+01-.42787097934602E+01
 -.41885309241911E+03-.75958099523776E+02-.55631252158745E+01 .48114785503447E+03
 .49628512886416E+03 .41829070732115E+01 .57493222652319E+02 .11191794722789E+01
 -.12890172252288E+02 .40260623129873E+02 .25520618876759E+01
 .38866224654437E+02-.11289043516269E+02-.35659549206377E-01 .11756688460449E+03
 .12659173477832E+03-.44981850387235E+00 .12341071247793E+02-.36384762320232E+01
 .31319549980396E+01 .87764338494750E+01-.72449912277981E+00
 -.11769541202100E+03-.96577271032884E+01 .78834689989398E+01 .28319725348426E+02
 .22974292045775E+02-.10257849135712E+00-.16475653442992E+01-.22541410549995E+02
 .19743873892509E+02 .68796834717914E+01-.40908491399911E+01
 .39336064116722E+03 .26127180309986E+02 .25515554756149E+01-.88005276287106E+02
 -.83740773232124E+02-.50974245023331E+00-.14754909073324E+02-.42543646946992E+01
 .92764811913795E+01-.56440897769032E+01-.30741845094606E+01
 -.14034585674589E+03 .17210049209555E+02 .11571764768592E+02 .72029475279936E+02
 .65852085070519E+02 .92514934352052E+00 .13432337355963E+01-.36230751180892E+02
 .32749697114220E+02 .16098723043222E+02-.71333023760451E+01

| | | | | | | | |
|----------|----------|---------|----------|----------|---------|-----------|----------|
| 1256. | 57.07 | 102.692 | 186.623 | 214.589 | 254.988 | 308.078 | 412.958 |
| 460.8 | 567.444 | 655.536 | | | | | |
| .2 | .005 | .005 | .005 | .005 | .005 | .005 | .005 |
| .005 | .005 | .005 | | | | | |
| 1. | .025213 | .309078 | .0558515 | .0324708 | .285298 | .00947477 | .0166416 |
| .0239448 | .0193181 | .095727 | | | | | |
| 0.6 | -.7508 | -.5217 | .1062 | -.1607 | .0729 | -.0979 | -.006 |
| .1083 | -.0457 | -.0064 | | | | | |
| .0022969 | .000288 | | | | | | |
| 0. | .1265 | | | | | | |

ORIGINAL PAGE IS
OF POOR QUALITY

.7073
 .2797
 .2615
 .3228
 .6369
 .0072
 .1578
 .4537
 .0317
 .0550
 .1019
 .0562
 .0068
 .0089

END OF FILE

C-2

APPENDIX E

SAMPLE OUTPUT FROM "SAFSS"

ORIGINAL
OF POOR
QUALITY

DAST ARM-1 OLD DATA SYMETRIC ROOT LOCUS

83/02/0 19.17.2

MACH = .025

11 VIBRATION MODES

15TH ORDER CONTROL LAW

CHARACTERISTIC LENGTH 97.600

ALTITUDES TO BE EVALUATED--
15000.0

MODAL FREQUENCIES

| | | | | | | | | | |
|---------|---------|---------|---------|--------|---------|---------|---------|---------|---------|
| 1256.00 | 57.0700 | 102.692 | 186.625 | 111.10 | 254.980 | 100.070 | 412.958 | 460.800 | 507.444 |
| 655.536 | | | | | | | | | |

MODAL DAMPING

| | | | | | | | | | |
|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| .200000 | .500000E-02 | .500000E-02 | .500000E-02 | .500000E-02 | .500000E-02 | .500000E-02 | .500000E-02 | .500000E-02 | .500000E-02 |
| .500000E-02 | | | | | | | | | |

GENERALIZED MASSES

| | | | | | | | | | |
|-------------|-------------|---------|-------------|-------------|---------|-------------|-------------|-------------|-------------|
| 1.00000 | .252130E-01 | .308078 | .556515E-01 | .147500E-01 | .105296 | .947477E-02 | .166485E-01 | .239448E-01 | .193181E-01 |
| .957270E-01 | | | | | | | | | |

P1 MATRIX

| | | | | | | | | | |
|-------------|--------------|----------|---------|-------------|-------------|-------------|--------------|----------|--------------|
| .926392E-01 | .116540E-01 | .125829 | .129916 | .107715 | .549066E-01 | .111332 | .339516E-01 | -.256613 | .237287 |
| .101182E-02 | | | | | | | | | |
| .586212 | -.251106 | .120243 | .120367 | .011897 | .168225 | .170361 | .141691 | -.928467 | .167309 |
| .703249 | | | | | | | | | |
| .201626 | .134796 | .170955 | .175310 | .505516E-02 | .102117 | .110194 | .244112 | -.458998 | .358740 |
| .115524 | | | | | | | | | |
| .326403 | .305015 | .194161 | .504702 | .274386 | .953581 | .407093E-01 | -.721628E-01 | .156880 | -.161647 |
| .534702 | | | | | | | | | |
| .246633 | -.600705 | | .131917 | .011001 | .570648 | .522234E-01 | .275070 | -.169589 | .153476 |
| .291976 | | | | | | | | | |
| .551953 | -.502362 | .170233 | .477084 | .479510 | .554011 | .157692 | .751653E-01 | -.651739 | -.928920E-01 |
| .820617 | | | | | | | | | |
| .984987 | -.670969E-01 | .200793 | .816513 | .905951 | .127973 | -.250808 | .514243 | -.993143 | .262856 |
| .246008 | | | | | | | | | |
| .434827 | .540660 | .442418 | .384356 | .142202 | .511937 | .100161 | -.270976 | -.312381 | -.386948 |
| .261361 | | | | | | | | | |
| .730501 | .115053E-01 | .669106 | .241560 | .147635 | .766705 | .883947 | -.178482 | -.238757 | -.401498 |
| .548199 | | | | | | | | | |
| .258070 | -.291920 | -.381909 | .889211 | .274586 | .151446 | .104678 | .559348 | -.685699 | .377972 |
| .601398 | | | | | | | | | |
| .354342 | -.123363E-01 | .374837 | .322976 | .547545 | .177904 | .635077 | -.109940 | -.520083 | .282936 |
| .322287 | | | | | | | | | |

P2 MATRIX

| | | | | | | | | | |
|----------|----------|----------|----------|-----------|-----------|-----------|-------------|-------------|----------|
| -28.2183 | -3.69223 | -3.85540 | 2.08832 | -2.34105 | 3.47485 | 5.07237 | -1.08431 | 1.38023 | -4.99129 |
| -1.85747 | | | | | | | | | |
| -071.747 | 9.91477 | 10.2208 | -48.8001 | 92.5553 | 6.54578 | -10.6912 | 1.80735 | 4.74593 | -10.6620 |
| .586858 | | | | | | | | | |
| 44.1055 | -7.34828 | -17.0800 | 48.4860 | -41.8086 | -4.34727 | -28.0257 | 2.16157 | .533629E-01 | -59.1764 |
| 14.6745 | | | | | | | | | |
| -278.248 | 18.6780 | 31.5086 | -114.414 | 111.603 | 4.01881 | -24.2607 | .681745E-01 | -3.58007 | 38.3014 |
| -17.1124 | | | | | | | | | |
| 74.0555 | -13.7936 | -25.0205 | 88.1688 | -86.4409 | .783316 | 29.3405 | .572230 | 4.84671 | -32.8731 |
| 14.5431 | | | | | | | | | |
| 68.9893 | -5.62004 | -6.27999 | 1.30568 | -2.14683 | -10.3899 | -13.4455 | 2.19150 | -10.4869 | 27.4676 |
| 0.15635 | | | | | | | | | |
| 393.226 | -14.7532 | -14.0446 | 13.5887 | -12.8759 | -10.9932 | -48.9604 | 9.08770 | -8.93270 | 17.8807 |
| 1.59805 | | | | | | | | | |
| -42.0321 | 5.29191 | -3.83293 | 1.72683 | -1.659679 | -6.645187 | -7.251774 | -4.31058 | -6.80849 | -8.66999 |
| 8.34785 | | | | | | | | | |
| 119.705 | -5.59387 | -8.99943 | 4.24710 | -5.25528 | -10.7372 | -14.1937 | .397841 | -18.8333 | 36.5766 |
| -14.6288 | | | | | | | | | |
| -402.277 | 6.50935 | 6.35758 | .703275 | 3.76626 | 15.6161 | 39.0244 | -10.2227 | 21.3796 | -99.0846 |
| 11.7163 | | | | | | | | | |
| 130.433 | -10.3006 | -12.9418 | 20.3344 | 19.7392 | -16.5050 | -25.0696 | .581637 | -13.1535 | 6.80773 |
| -5.57390 | | | | | | | | | |

P3 MATRIX-----

| | | | | | | | | | |
|----------|-----------|----------|----------|----------|-------------|----------|----------|----------|----------|
| -54.8442 | -4.14789 | -6.45235 | 27.0635 | -20.6857 | -864973E-01 | 24.1138 | -2.56370 | 2.25067 | -3.49066 |
| 2.38041 | | | | | | | | | |
| 3813.79 | -11.7194 | -22.4274 | 174.883 | -181.473 | 1.93830 | 118.862 | 15.3487 | -129.495 | 626.353 |
| -142.207 | | | | | | | | | |
| 144.210 | 5.07701 | -7.06098 | 62.1113 | -84.8174 | -18.7183 | 1.13760 | 20.8252 | -130.462 | 563.123 |
| -104.846 | | | | | | | | | |
| 1300.42 | -2.65859 | 1000.376 | 42.6269 | 61.7806 | 17.5758 | 1.81487 | -13.0717 | 74.0671 | -299.249 |
| 50.5610 | | | | | | | | | |
| 510.183 | 1.00302 | -4.29628 | 63.5948 | -83.3264 | -14.7557 | 24.2325 | 12.6682 | -83.9559 | 360.257 |
| -67.1345 | | | | | | | | | |
| 273.055 | -3.35841 | -2.21603 | 17.1903 | -17.2644 | -2.85395 | 4.64018 | 2.67845 | -2.16669 | -3.19188 |
| 0.62689 | | | | | | | | | |
| 1552.39 | -1.900168 | -2.69789 | 5.71782 | -8.79682 | -6.70539 | -28.8804 | 8.58814 | -8.68888 | 23.5493 |
| 10.4471 | | | | | | | | | |
| 182.242 | 4.58305 | .969789 | -17.5346 | 15.7751 | -5.61938 | -11.6669 | 1.42089 | -21.5581 | 78.1576 |
| -26.2261 | | | | | | | | | |
| 515.645 | 3.29720 | 2.02691 | -31.0101 | 32.6012 | -9.14404 | -34.0852 | 2.96137 | -3.67777 | -17.3326 |
| -3.42028 | | | | | | | | | |
| -1747.64 | -3.74706 | -9.51482 | 71.7000 | -79.9085 | 5.11534 | 83.0102 | -4.99336 | -35.4208 | 175.375 |
| -43.4916 | | | | | | | | | |
| 590.619 | -1.45682 | -3.65376 | 30.1062 | -37.6847 | -13.6446 | -21.5805 | 8.55404 | -48.9301 | 167.734 |
| -50.8718 | | | | | | | | | |

ORIGINAL
OF POOR
QUALITY

RO MATRIX-----

| | | | | | | | | | |
|----------|----------|--------------|----------|----------|----------|----------|----------|----------|----------|
| 20.5643 | 4.47421 | 1.44489 | -29.4951 | -31.1615 | -.761332 | -4.30538 | -3.53698 | 4.24420 | -1.48221 |
| -.878882 | | | | | | | | | |
| 871.981 | 37.7393 | 1.08041 | 19.8398 | 49.3950 | -2.75265 | 3.31657 | -.598906 | 4.95210 | -6.16472 |
| -2.19524 | | | | | | | | | |
| -73.1204 | -108.869 | -20.1985 | 962.302 | 1029.43 | 3.75900 | 117.930 | 29.8954 | -42.4864 | 66.4163 |
| 8.27012 | | | | | | | | | |
| 284.868 | 64.6764 | 5.05188 | -506.689 | -536.563 | -6.92402 | -56.3762 | -5.46069 | 15.3466 | -39.2774 |
| 2.14038 | | | | | | | | | |
| -50.6096 | -46.4849 | -4.60378 | 434.343 | 466.390 | 5.12325 | 47.5757 | 4.17718 | -11.5854 | 31.5851 |
| 1.34488 | | | | | | | | | |
| 67.1206 | -7.07783 | 10.2361 | 16.6132 | 9.89673 | 1.11377 | -4.84042 | 26.3341 | 21.7107 | 6.81425 |
| -4.27871 | | | | | | | | | |
| -418.853 | -75.8581 | -5.56313 | 481.148 | 496.285 | 4.18281 | 57.4932 | 1.11918 | -12.8802 | 40.2606 |
| 3.55208 | | | | | | | | | |
| 30.8662 | -11.2800 | -.336595E-01 | 117.567 | 126.592 | -.449819 | 12.3419 | -3.63848 | 3.13195 | 8.77643 |
| .724499 | | | | | | | | | |
| 117.695 | -9.63773 | 7.08347 | 28.3187 | 22.9743 | -.102576 | -1.64757 | -22.5414 | 19.7439 | 6.87968 |
| 4.09085 | | | | | | | | | |
| 393.361 | 26.1272 | 2.55156 | -98.0053 | -83.7408 | -.509742 | -14.7549 | -4.25438 | 8.27648 | -5.64409 |
| 3.07418 | | | | | | | | | |
| -140.346 | -17.2100 | 11.5718 | 72.0295 | 65.8321 | .925149 | 1.34323 | -36.2308 | 32.7497 | 16.0987 |
| -7.13330 | | | | | | | | | |

* END OF INPUT DATA *

1 NEW CASE NEW CASE NEW CASE NEW CASE NEW CASE NEW CASE NEW CASE NEW CASE NEW CASE NEW CASE

MACH = .825000
ALT = 15000.0
QBAR = 4.22986
VTRUE = 10467.0

THE GAIN FACTOR = 0.000

EIGENVALUES COMPUTED, ERROR CODE= 0

| REAL PART RAD/SEC | IMAGINARY PART RAD/SEC | FREQUENCY RAD/SEC | FREQUENCY CYCLE/SEC | DAMPING FACTOR |
|----------------------|---------------------------|----------------------|------------------------|----------------|
| -10812.44 | 0.00 | 10812.44 | 1733.67 | 1.0000 |
| 263.78 | 3716.92 | 3726.26 | 597.47 | -.0708 |
| 263.78 | 1716.92 | 3726.26 | 597.47 | -.0708 |
| -2635.31 | 0.00 | 2635.31 | 422.53 | 1.0000 |
| -1500.09 | 0.00 | 1500.09 | 240.52 | 1.0000 |

| | | | | |
|----------|----------|---------|--------|---------|
| -1499.91 | 0.00 | 1499.91 | 240.50 | 1.0000 |
| 1145.58 | 0.00 | 1145.58 | 183.68 | -1.0000 |
| -2.02 | 655.42 | 655.42 | 105.09 | .0031 |
| -2.02 | -655.42 | 655.42 | 105.09 | .0031 |
| 136.18 | 533.34 | 550.45 | 88.26 | -.2474 |
| 136.18 | -533.34 | 550.45 | 88.26 | -.2474 |
| -448.65 | 300.27 | 539.86 | 86.56 | .8310 |
| -448.65 | -300.27 | 539.86 | 86.56 | .8310 |
| -18.68 | 496.15 | 496.50 | 79.61 | .0376 |
| -18.68 | -496.15 | 496.50 | 79.61 | .0376 |
| -4.64 | 459.27 | 459.29 | 73.64 | .0101 |
| -4.64 | -459.27 | 459.29 | 73.64 | .0101 |
| -294.70 | 326.46 | 439.80 | 70.52 | .6701 |
| -294.70 | -326.46 | 439.80 | 70.52 | .6701 |
| -3.96 | 414.33 | 414.35 | 66.44 | .0096 |
| -3.96 | -414.33 | 414.35 | 66.44 | .0096 |
| -120.00 | 320.26 | 342.00 | 54.84 | .3508 |
| -120.00 | -320.26 | 342.00 | 54.84 | .3508 |
| -12.91 | 307.74 | 308.01 | 49.38 | .0419 |
| -12.91 | -307.74 | 308.01 | 49.38 | .0419 |
| -295.30 | .00 | 295.30 | 47.35 | 1.0000 |
| -295.30 | -.00 | 295.30 | 47.35 | 1.0000 |
| -1.45 | 254.78 | 254.78 | 40.85 | .0057 |
| -1.45 | -254.78 | 254.78 | 40.85 | .0057 |
| -2.52 | 202.62 | 202.64 | 32.49 | .0125 |
| -2.52 | -202.62 | 202.64 | 32.49 | .0125 |
| -177.84 | 0.00 | 177.84 | 20.53 | 1.0000 |
| -15.60 | 145.16 | 145.99 | 23.41 | .1089 |
| -15.60 | 145.16 | 145.99 | 23.41 | .1089 |
| -50.00 | 100.22 | 112.00 | 17.89 | .4464 |
| -50.00 | -100.22 | 112.00 | 17.89 | .4464 |
| -2.19 | 102.28 | 102.30 | 16.40 | .0213 |
| -2.19 | -102.28 | 102.30 | 16.40 | .0213 |
| -4.33 | 97.31 | 97.41 | 15.62 | .0444 |
| -4.33 | -97.31 | 97.41 | 15.62 | .0444 |
| -71.20 | 0.00 | 71.20 | 11.42 | 1.0000 |
| -50.00 | 29.39 | 58.00 | 9.30 | .8621 |
| -50.00 | -29.39 | 58.00 | 9.30 | .8621 |
| -2.00 | 0.00 | 2.00 | .32 | 1.0000 |
| -38.39 | 292.79 | 295.30 | 47.35 | .1300 |
| -38.39 | -292.79 | 295.30 | 47.35 | .1300 |
| -251.20 | 1230.62 | 1256.00 | 201.39 | .2006 |
| -251.20 | -1230.62 | 1256.00 | 201.39 | .2006 |

ORIGINAL PRICE IS
OF POOR QUALITY

EIGENVALUES COMPUTED, ERROR CODE. 0

| REAL PART RAD/SEC | IMAGINARY PART RAD/SEC | FREQUENCY RAD/SEC | FREQUENCY CYCLE/SEC | DAMPING FACTOR |
|----------------------|---------------------------|----------------------|------------------------|----------------|
| 0812.44 | 0.00 | 10812.44 | 1733.67 | 1.0000 |
| 283.78 | 3718.81 | 3726.26 | 587.47 | -.0708 |
| 263.78 | -3718.81 | 3726.26 | 587.47 | -.0708 |
| -2634.84 | 0.00 | 2634.84 | 422.47 | 1.0000 |
| 1145.74 | 0.00 | 1145.74 | 183.71 | 1.0000 |
| -1632.04 | 0.00 | 1632.04 | 261.68 | 1.0000 |
| -244.68 | 1234.72 | 1234.72 | 201.82 | .1944 |
| -244.68 | -1234.72 | 1234.72 | 201.82 | .1944 |
| -1307.10 | 0.00 | 1307.10 | 209.58 | 1.0000 |
| -590.76 | 237.34 | 636.65 | 102.08 | .9279 |
| -590.76 | -237.34 | 636.65 | 102.08 | .9279 |
| -2.02 | 655.35 | 655.36 | 105.08 | .0031 |
| -2.02 | -655.35 | 655.36 | 105.08 | .0031 |
| -408.10 | 356.84 | 542.11 | 86.92 | .7528 |
| -408.10 | -356.84 | 542.11 | 86.92 | .7528 |
| 136.05 | 533.51 | 550.59 | 88.28 | -.2471 |
| 136.05 | -533.51 | 550.59 | 88.28 | -.2471 |
| -18.65 | 496.42 | 496.77 | 79.65 | .0375 |
| -18.65 | -496.42 | 496.77 | 79.65 | .0375 |
| -3.96 | 459.87 | 459.89 | 73.74 | .0086 |
| -3.96 | -459.87 | 459.89 | 73.74 | .0086 |
| -3.84 | 414.33 | 414.35 | 66.44 | .0095 |
| -3.84 | -414.33 | 414.35 | 66.44 | .0095 |
| -110.94 | 359.60 | 378.33 | 60.34 | .2948 |
| -110.94 | -359.60 | 378.33 | 60.34 | .2948 |
| -12.80 | 307.52 | 307.79 | 49.35 | .0416 |
| -12.80 | -307.52 | 307.79 | 49.35 | .0416 |
| -118.84 | 254.73 | 254.22 | 40.76 | .4675 |
| -118.84 | -254.73 | 254.22 | 40.76 | .4675 |
| -1.45 | 254.78 | 254.78 | 40.85 | .0057 |
| -1.45 | -254.78 | 254.78 | 40.85 | .0057 |
| -3.00 | 202.76 | 202.78 | 32.51 | .0148 |
| -3.00 | -202.76 | 202.78 | 32.51 | .0148 |
| -141.44 | 0.00 | 141.44 | 22.68 | 1.0000 |
| -19.50 | 146.45 | 147.75 | 23.69 | .1320 |
| -19.50 | -146.45 | 147.75 | 23.69 | .1320 |
| -9.47 | 125.79 | 126.15 | 20.23 | .0751 |
| -9.47 | -125.79 | 126.15 | 20.23 | .0751 |
| -2.01 | 101.40 | 101.42 | 16.26 | .0198 |
| -2.01 | -101.40 | 101.42 | 16.26 | .0198 |
| -78.64 | 0.00 | 78.64 | 12.61 | 1.0000 |
| -33.60 | 68.06 | 75.90 | 12.17 | .4427 |
| -33.60 | -68.06 | 75.90 | 12.17 | .4427 |

ORIGINAL PAGE IS
OF POOR QUALITY

| | | | | |
|--------|---------|--------|-------|--------|
| -39.81 | 34.05 | 52.23 | 8.37 | .7584 |
| -39.81 | -34.05 | 52.23 | 8.37 | .7584 |
| -2.00 | 0.00 | 2.00 | .32 | 1.0000 |
| -38.39 | 292.79 | 295.30 | 47.35 | .1300 |
| -38.39 | -292.79 | 295.30 | 47.35 | .1300 |

THE GAIN FACTOR = .500

EIGENVALUES COMPUTED, ERROR CODE = 0

| REAL PART RAD/SEC | IMAGINARY PART RAD/SEC | FREQUENCY RAD/SEC | FREQUENCY CYCLE/SEC | DAMPING FACTOR |
|----------------------|---------------------------|----------------------|------------------------|----------------|
| -10812.44 | 0.00 | 10812.44 | 1733.67 | 1.0000 |
| 263.79 | 3716.91 | 3726.26 | 587.47 | -.0708 |
| 263.79 | -3716.91 | 3726.26 | 587.47 | -.0708 |
| -2634.35 | 0.00 | 2634.35 | 422.38 | 1.0000 |
| 1145.90 | 0.00 | 1145.90 | 183.73 | -1.0000 |
| -1678.04 | 0.00 | 1678.04 | 268.06 | 1.0000 |
| -238.51 | 1238.83 | 1261.58 | 202.28 | .1891 |
| -238.51 | -1238.83 | 1261.58 | 202.28 | .1891 |
| -1176.06 | 0.00 | 1176.06 | 188.57 | 1.0000 |
| -888.79 | 245.67 | 731.29 | 117.25 | .9419 |
| -888.79 | -245.67 | 731.29 | 117.25 | .9419 |
| -2.02 | 655.30 | 655.30 | 105.07 | .0031 |
| -2.02 | -655.30 | 655.30 | 105.07 | .0031 |
| 135.94 | 533.71 | 550.75 | 88.31 | -.2168 |
| 135.94 | -533.71 | 550.75 | 88.31 | -.2168 |
| -419.30 | 364.61 | 555.65 | 89.09 | .7546 |
| -419.30 | -364.61 | 555.65 | 89.09 | .7546 |
| -18.54 | 496.69 | 497.63 | 79.69 | .0373 |
| -18.54 | -496.69 | 497.63 | 79.69 | .0373 |
| -3.05 | 460.36 | 460.37 | 73.82 | .0066 |
| -3.05 | -460.36 | 460.37 | 73.82 | .0066 |
| -3.91 | 414.34 | 414.36 | 66.44 | .0094 |
| -3.91 | -414.34 | 414.36 | 66.44 | .0094 |
| -88.94 | 370.88 | 381.40 | 61.15 | .2332 |
| -88.94 | -370.88 | 381.40 | 61.15 | .2332 |
| -12.65 | 307.24 | 307.51 | 49.31 | .0411 |
| -12.65 | -307.24 | 307.51 | 49.31 | .0411 |
| -1.44 | 254.77 | 254.78 | 40.85 | .0057 |
| -1.44 | -254.77 | 254.78 | 40.85 | .0057 |
| -87.78 | 227.64 | 243.98 | 39.12 | .3598 |
| -87.78 | -227.64 | 243.98 | 39.12 | .3598 |
| -3.71 | 202.77 | 202.80 | 32.52 | .0183 |
| -3.71 | -202.77 | 202.80 | 32.52 | .0183 |

ORIGINAL FILED IN
OF POOR QUALITY

| | | | | |
|---------|---------|--------|-------|--------|
| -138.11 | 0.00 | 138.11 | 22.15 | 1.0000 |
| -23.01 | 151.38 | 153.12 | 24.55 | .1503 |
| -23.01 | -151.38 | 153.12 | 24.55 | .1503 |
| -5.55 | 135.30 | 135.41 | 21.71 | .0410 |
| -5.55 | -135.30 | 135.41 | 21.71 | .0410 |
| -1.94 | 101.42 | 101.44 | 16.26 | .0192 |
| -1.94 | -101.42 | 101.44 | 16.26 | .0192 |
| -80.60 | 0.00 | 80.60 | 12.92 | 1.0000 |
| -37.84 | 54.62 | 66.45 | 10.65 | .5695 |
| -37.84 | -54.62 | 66.45 | 10.65 | .5695 |
| -28.72 | 38.35 | 48.52 | 7.78 | .6126 |
| -28.72 | -38.35 | 48.52 | 7.78 | .6126 |
| -2.00 | 0.00 | 2.00 | .32 | 1.0000 |
| -38.33 | 292.79 | 295.30 | 47.35 | .1300 |
| -38.33 | -292.79 | 295.30 | 47.35 | .1300 |

THE GAIN FACTOR = 1.000

EIGENVALUES COMPUTED, ERROR CODE= 0

| REAL PART RAD/SEC | IMAGINARY PART RAD/SEC | FREQUENCY RAD/SEC | FREQUENCY CYCLE/SEC | DAMPING FACTOR |
|----------------------|---------------------------|----------------------|------------------------|----------------|
| -10812.44 | 0.00 | 10812.44 | 1733.67 | 1.0000 |
| 263.80 | 3716.90 | 3726.25 | 587.47 | -.0708 |
| 263.80 | -3716.90 | 3726.25 | 587.47 | -.0708 |
| -2633.39 | 0.00 | 2633.39 | 422.24 | 1.0000 |
| -1737.33 | 0.00 | 1737.33 | 278.57 | 1.0000 |
| -227.27 | 1247.02 | 1267.56 | 203.24 | .1793 |
| -227.27 | -1247.02 | 1267.56 | 203.24 | .1793 |
| 1146.22 | 0.00 | 1146.22 | 183.78 | -1.0000 |
| -915.25 | 337.20 | 975.39 | 156.39 | .8383 |
| -915.25 | -337.20 | 975.39 | 156.39 | .8383 |
| -803.99 | 0.00 | 803.99 | 128.91 | 1.0000 |
| -2.03 | 655.20 | 655.20 | 103.06 | .0031 |
| -2.03 | -655.20 | 655.20 | 103.06 | .0031 |
| -427.67 | 367.26 | 563.72 | 90.39 | .7586 |
| -427.67 | -367.26 | 563.72 | 90.39 | .7586 |
| 135.74 | 534.14 | 551.12 | 88.37 | -.2463 |
| 135.74 | -534.14 | 551.12 | 88.37 | -.2463 |
| -18.12 | 497.05 | 497.30 | 79.75 | .0364 |
| -18.12 | -497.05 | 497.30 | 79.75 | .0364 |
| -.75 | 460.61 | 460.61 | 73.85 | .0016 |
| -.75 | -460.61 | 460.61 | 73.85 | .0016 |
| -3.84 | 414.33 | 414.34 | 66.44 | .0093 |
| -3.84 | -414.33 | 414.34 | 66.44 | .0093 |

101

| | | | | |
|---------|---------|--------|-------|--------|
| -57.35 | 373.95 | 378.32 | 60.66 | .1516 |
| -57.35 | -373.95 | 378.32 | 60.66 | .1516 |
| -12.09 | 306.48 | 306.72 | 48.10 | .0384 |
| -12.09 | -306.48 | 306.72 | 48.10 | .0384 |
| -1.43 | 254.76 | 254.76 | 40.85 | .0056 |
| -1.43 | -254.76 | 254.76 | 40.85 | .0056 |
| -54.07 | 237.23 | 243.31 | 39.01 | .2222 |
| -54.07 | -237.23 | 243.31 | 39.01 | .2222 |
| -5.48 | 201.22 | 201.30 | 32.28 | .0277 |
| -5.48 | -201.22 | 201.30 | 32.28 | .0277 |
| -136.03 | 0.00 | 136.03 | 21.81 | 1.0000 |
| -28.75 | 161.53 | 164.07 | 26.31 | .1752 |
| -28.75 | -161.53 | 164.07 | 26.31 | .1752 |
| -5.78 | 142.03 | 142.15 | 22.79 | .0407 |
| -5.78 | -142.03 | 142.15 | 22.79 | .0407 |
| -1.91 | 101.43 | 101.45 | 16.27 | .0188 |
| -1.91 | -101.43 | 101.45 | 16.27 | .0188 |
| -82.01 | 0.00 | 82.01 | 13.15 | 1.0000 |
| -45.18 | 51.63 | 68.61 | 11.00 | .6585 |
| -45.18 | -51.63 | 68.61 | 11.00 | .6585 |
| -16.93 | 33.13 | 37.21 | 5.97 | .4549 |
| -16.93 | -33.13 | 37.21 | 5.97 | .4549 |
| -2.00 | 0.00 | 2.00 | .32 | 1.0000 |
| -38.39 | 292.79 | 295.30 | 47.35 | .1300 |
| -38.39 | -292.79 | 295.30 | 47.35 | .1300 |

THE GAIN FACTOR = 2.000

EIGENVALUES COMPUTED. ERROR CODE = 0

| REAL PART RAD/SEC | IMAGINARY PART RAD/SEC | FREQUENCY RAD/SEC | FREQUENCY CYCLE/SEC | DAMPING FACTOR |
|----------------------|---------------------------|----------------------|------------------------|----------------|
| -10812.44 | 0.00 | 10812.44 | 1733.67 | 1.0000 |
| 263.81 | 3716.89 | 3726.24 | 597.47 | -.0708 |
| 263.81 | -3716.89 | 3726.24 | 597.47 | -.0708 |
| -2631.41 | 0.00 | 2631.41 | 421.82 | 1.0000 |
| -1812.64 | 0.00 | 1812.64 | 289.64 | 1.0000 |
| 1146.86 | 0.00 | 1146.86 | 183.80 | -1.0000 |
| -208.12 | 1262.85 | 1279.88 | 203.22 | .1628 |
| -208.12 | -1262.85 | 1279.88 | 203.22 | .1628 |
| -1014.27 | 553.18 | 1155.32 | 185.24 | .8778 |
| -1014.27 | -553.18 | 1155.32 | 185.24 | .8778 |
| -709.98 | 0.00 | 709.98 | 113.84 | 1.0000 |
| -2.10 | 655.06 | 655.06 | 105.03 | .0032 |
| -2.10 | -655.06 | 655.06 | 105.03 | .0032 |

ORIGINAL
OF FOUR COPIES

| | | | | |
|---------|---------|--------|-------|--------|
| -432.60 | 367.60 | 567.69 | 91.02 | .7820 |
| -432.60 | -367.60 | 567.69 | 91.02 | .7820 |
| 135.58 | 535.15 | 552.06 | 80.52 | -.2456 |
| 135.58 | -535.15 | 552.06 | 89.52 | -.2456 |
| -17.32 | 487.01 | 487.31 | 79.74 | .0348 |
| -17.32 | -487.01 | 487.31 | 79.74 | .0348 |
| 2.95 | 457.65 | 457.66 | 73.38 | -.0064 |
| 2.95 | -457.65 | 457.66 | 73.38 | -.0064 |
| -3.75 | 414.09 | 414.11 | 68.40 | .0090 |
| -3.75 | -414.09 | 414.11 | 68.40 | .0090 |
| -9.24 | 361.74 | 361.86 | 58.02 | .0255 |
| -9.24 | -361.74 | 361.86 | 58.02 | .0255 |
| -6.17 | 305.81 | 305.87 | 48.04 | .0202 |
| -6.17 | -305.81 | 305.87 | 48.04 | .0202 |
| -31.78 | 275.19 | 277.02 | 44.42 | .1147 |
| -31.78 | -275.19 | 277.02 | 44.42 | .1147 |
| -1.38 | 254.80 | 254.81 | 40.88 | .0034 |
| -1.38 | -254.80 | 254.81 | 40.88 | .0034 |
| -2.68 | 198.69 | 198.71 | 31.86 | .0133 |
| -2.68 | -198.69 | 198.71 | 31.86 | .0133 |
| -134.84 | 0.00 | 134.84 | 21.62 | 1.0000 |
| -40.86 | 164.96 | 169.94 | 27.25 | .2405 |
| -40.86 | -164.96 | 169.94 | 27.25 | .2405 |
| -7.89 | 144.33 | 144.54 | 23.18 | .0546 |
| -7.89 | -144.33 | 144.54 | 23.18 | .0546 |
| -1.89 | 101.44 | 101.46 | 16.27 | .0187 |
| -1.89 | -101.44 | 101.46 | 16.27 | .0187 |
| -82.89 | 0.00 | 82.89 | 13.29 | 1.0000 |
| -47.78 | 51.01 | 69.89 | 11.21 | .6836 |
| -47.78 | -51.01 | 69.89 | 11.21 | .6836 |
| -9.70 | 28.41 | 28.14 | 4.51 | .3447 |
| -9.70 | -28.41 | 28.14 | 4.51 | .3447 |
| -1.99 | 0.00 | 1.99 | .32 | 1.0000 |
| -38.39 | 292.79 | 295.30 | 47.35 | .1300 |
| -38.39 | -292.79 | 295.30 | 47.35 | .1300 |

THE ZEROS ARE LOCATED AT:

| REAL PART | IMAGINARY PART |
|-----------|----------------|
| RAD/SEC | RAD/SEC |
| -11034.83 | 0.00 |
| -4793.10 | 7047.97 |
| -4793.10 | -7047.97 |
| 3346.91 | 7142.08 |
| 3346.91 | -7142.08 |
| -8401.13 | 0.00 |

| | |
|----------|----------|
| 7407.26 | 0.00 |
| 143.42 | 3539.80 |
| 143.42 | -3539.80 |
| -2950.16 | 0.00 |
| 791.25 | 173.16 |
| 791.25 | -173.16 |
| -668.29 | 0.00 |
| -2.70 | 654.83 |
| -2.70 | -654.83 |
| -437.72 | 366.90 |
| -437.72 | -366.90 |
| 141.57 | 534.13 |
| 141.57 | -534.13 |
| -17.01 | 495.71 |
| -17.01 | -495.71 |
| -3.46 | 452.61 |
| -3.46 | -452.61 |
| -4.08 | 414.20 |
| -4.08 | -414.20 |
| -13.26 | 309.79 |
| -13.26 | -309.79 |
| -1.44 | 254.80 |
| -1.44 | -254.80 |
| -60.00 | 300.06 |
| -60.00 | -300.06 |
| -1.21 | 200.60 |
| -1.21 | -200.60 |
| -133.52 | 0.00 |
| -9.80 | 145.03 |
| -9.80 | -145.03 |
| -1.82 | 101.45 |
| -1.82 | -101.45 |
| -83.92 | 0.00 |
| -50.00 | 160.39 |
| -50.00 | -160.39 |
| -50.00 | 50.41 |
| -50.00 | -50.41 |
| .08 | .14 |
| .08 | .14 |
| -.16 | 0.00 |
| -38.39 | 292.79 |
| -38.39 | -292.79 |

END OF FILE

ORIGINAL PAGE
OF POOR QUALITY

BIBLIOGRAPHY

1. Bisplinghoff, R. L.; Ashley, H.; and Hoffman, R. L.:
Flight Dynamics. Addison-Wesley.; Reading, Mass., 1955.
2. Edwards, John W.: "Applications of Laplace Transform
Methods to Airfoil Motion and Stability Calculations".
AIAA Paper 79-077, St. Louis, Missouri, 1979.
3. Edwards, John W.: "Steady Aerodynamic Modeling for
Unsteady Airfoil Motion". AIAA Journal., vol. 15, no. 4,
April 1977, pp. 593-595.
4. Gilyard, Glenn B.; and Edwards, John W.: "Real Time
Flutter Analysis of an Active Flutter-Suppression
System on a Remotely Piloted Research Aircraft".
NASA TM-84901, January 1983.
5. Gilyard, Glenn B.; and Potzky, A. S.: "Comparison of
Analysis and Flight Test for a Drone Aircraft with
Active Flutter Suppression". AIAA Paper 81-0640,
Atlanta, Georgia 1981.
6. Wykes, John H.; Byar, Thomas R.; Macmillan, Cary J.;
and Greck, David C.: "Analysis and Tests of the B-1
Aircraft Servo-Flap Mode Control System". NASA
CR-144887, January 1980.

End of Document